

# ISO 8913:2006-11 (E)

Aerospace - Lightweight polytetrafluoroethylene (PTFE) hose assemblies, classification 400 °F/3 000 psi (204 °C/20 684 kPa) and 204 °C/21 000 kPa (400 °F/3 046 psi) - Procurement specification

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Classification .....</b>	<b>2</b>
<b>4</b>	<b>Requirements .....</b>	<b>2</b>
4.1	Qualification .....	2
4.2	Materials .....	2
4.3	Construction .....	3
4.4	Inner tube .....	4
4.5	Hose .....	5
4.6	Screw threads .....	7
4.7	Part numbering of interchangeable parts .....	7
4.8	Identification of products .....	7
4.9	Workmanship .....	8
4.10	Hose assembly -- Test and performance requirements .....	8
<b>5</b>	<b>Quality assurance .....</b>	<b>13</b>
5.1	Responsibility for inspection .....	13
5.2	Classification of inspections .....	13
5.3	Qualification inspections .....	13
5.4	Quality conformance inspections .....	15
5.5	Test conditions .....	17
5.6	Inspection methods .....	18
<b>6</b>	<b>Preparation for delivery .....</b>	<b>18</b>
6.1	Storage and packaging .....	18
6.2	Marking .....	18
<b>7</b>	<b>Ordering data .....</b>	<b>18</b>
<b>Annex B (normative) Equivalent national qualification procedure and fire resistance specification ..</b>		<b>21</b>
<b>Annex C (informative) Equivalent materials .....</b>		<b>22</b>
<b>Bibliography .....</b>		<b>25</b>