

ISO 8913:2006-11 (E)

Aerospace - Lightweight polytetrafluoroethylene (PTFE) hose assemblies,
classification 400 °F/3 000 psi (204 °C/20 684 kPa) and 204 °C/21 000 kPa (400 °F/3 046
psi) - Procurement specification

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Classification | 2 |
| 4 | Requirements | 2 |
| 4.1 | Qualification | 2 |
| 4.2 | Materials | 2 |
| 4.3 | Construction | 3 |
| 4.4 | Inner tube | 4 |
| 4.5 | Hose | 5 |
| 4.6 | Screw threads | 7 |
| 4.7 | Part numbering of interchangeable parts | 7 |
| 4.8 | Identification of products | 7 |
| 4.9 | Workmanship | 8 |
| 4.10 | Hose assembly -- Test and performance requirements | 8 |
| 5 | Quality assurance | 13 |
| 5.1 | Responsibility for inspection | 13 |
| 5.2 | Classification of inspections | 13 |
| 5.3 | Qualification inspections | 13 |
| 5.4 | Quality conformance inspections | 15 |
| 5.5 | Test conditions | 17 |
| 5.6 | Inspection methods | 18 |
| 6 | Preparation for delivery | 18 |
| 6.1 | Storage and packaging | 18 |
| 6.2 | Marking | 18 |
| 7 | Ordering data | 18 |
| Annex B (normative) Equivalent national qualification procedure and fire resistance specification .. | | 21 |
| Annex C (informative) Equivalent materials | | 22 |
| Bibliography | | 25 |