

ISO 7169:2007-02 (E)

Aerospace - Separable tube fittings for fluid systems, for 24° cones, for pressures up to 3000 psi or 2100 0 kPa - Procurement specification, inch/metric

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Classification	1
4	Requirements	2
4.1	Qualification	2
4.1.1	Manufacturer qualification	2
4.1.2	Product qualification	2
4.2	Materials	2
4.2.1	Fittings	2
4.2.2	Tubing	2
4.3	Design and manufacture	5
4.3.1	Threads	5
4.3.2	Fluid passages	5
4.4	Surface protection and colour identification	5
4.4.1	Surface protection	5
4.4.2	Colour identification	6
4.5	Marking	6
4.6	Performance	6
4.6.1	Proof pressure	6
4.6.2	Gaseous pressure	7
4.6.3	Hydraulic impulse resistance	7
4.6.4	Minimum burst pressure	7
4.6.5	Flexure fatigue resistance	7
4.6.6	Re-use capability	8
4.6.7	Tensile load capability	8
4.7	Workmanship	8
5	Quality assurance provisions	9
5.1	Responsibility for inspection	9
5.2	Inspection lot	9
5.2.1	Material certification	10
5.2.2	Heat-treating certification	10
5.3	Classification of inspections and tests	10
5.3.1	Qualification inspection	10
5.3.2	Quality conformance inspection	10
5.4	Quality control records	11
5.5	Quality conformance inspection procedures	11
5.5.1	Examination of product	11
5.5.2	Material certification	11
5.5.3	Rolled threads	11
5.5.4	Fluid passages	11
5.5.5	Sampling instructions	12
5.6	Test conditions	12
5.6.1	Test fluids	12

5.6.2	Specimen preparation	12
5.6.3	Lubricants	15
5.6.4	Qualification test procedures	15
5.6.5	Sampling instructions	15
6	Preparation for delivery	15
6.1	Cleaning	15
6.2	Preservative material	16
6.3	Packaging	16
6.4	Package identification	16
6.5	Packing for shipment	16
6.6	Inspection	16
Annex A (informative) Equivalent materials and processes		17
Bibliography		20