

DIN 25449:2008-02 (E)

Reinforced and prestressed concrete components in nuclear facilities - Safety concept, actions, design and construction

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms, definitions and symbols	6
4	Materials	6
4.1	Concrete	6
4.1.1	General	6
4.1.2	Temperature dependence of characteristic values	7
4.1.3	Bound water content	7
4.1.4	Heat capacity	8
4.2	Reinforcing steel	9
4.3	Prestressing steel	9
5	Accidental actions	9
5.1	General	9
5.2	Internal actions	9
5.2.1	Differential pressure	9
5.2.2	Jet impingement forces	10
5.2.3	Temperature	10
5.2.4	Anchorage forces	11
5.2.5	Impact loads	11
5.3	External actions	11
5.3.1	Seismic design situation	11
5.3.2	Aircraft crash	12
5.3.3	Explosion pressure wave	13
5.3.4	Flooding	13
6	Safety concept	13
6.1	General	13
6.2	Actions	13
6.3	Combination rules	14
6.4	Partial factors and combination factors for actions	15
6.5	Ultimate limit state	15
6.6	Serviceability limit state	17
7	Procedures for structural analysis and verification	17
7.1	General	17
7.2	Linear-elastic analysis	17
7.3	Non-linear analysis	17
7.4	Dynamic behaviour of building elements	18
7.4.1	General	18
7.4.2	Building element stiffness	18
7.4.3	Masses	18
7.4.4	Damping of building elements	18
7.4.5	Soil and foundation	19
7.4.6	Simplified methods for individual building elements	19

8	Design recommendations	21
8.1	Design strength of reinforced concrete	21
8.2	Ultimate limit strain of reinforcing steel and concrete	21
8.3	Shear forces	21
8.4	Punching shear	22
8.4.1	General	22
8.4.2	Building elements without punching shear reinforcement	22
8.4.3	Building elements with punching shear reinforcement	24
8.4.4	Structural detailing	25
Annex A (informative) Load assumptions due to blast waves from explosions for overall buildings and slender building elements		27
A.1	General	27
A.2	Rectangular buildings	28
A.2.1	Directly loaded individual building elements	28
A.2.2	Overall structure, bracing building elements, foundation	28
A.3	Cylindrical and spherical buildings	28
A.4	Slender building elements	30
Bibliography		31
Figures Figure 1 -- Bound water content at low water vapour partial pressure and at temperatures kept constant at progressive steps		8
Figure 2 -- Idealized differential pressure p as a function of time		10
Figure 3 -- Idealized jet impingement force as a function of time		10
Figure 4 -- Idealized form of an elastic ground response or floor response spectrum		12
Figure 5 -- Load/time function for an aircraft crash according to the RSK-Leitlinien		12
Figure 6 -- Load/time function of pressure waves caused by chemical reactions, as defined in the BMI-Richtlinie (p: overpressure acting on the building)		13
Figure 7 -- Dynamic load factor for a pressure wave caused by an explosion (p : resulting overpressure)		20
Figure A.1 -- Idealized overpressure, p, as a function of time of blast pressure waves acting on buildings		27
Figure A.2 -- Pressure/time function of resulting overpressure $p = p_{vorn} - p_{rück}$ for rectangular buildings		28
Figure A.3 -- Overpressure p on cylindrical and spherical buildings, as a function of time		29
Figure A.4 -- Overpressure distribution on the perimeter of cylindrical and spherical buildings		29
Tables Table 1 -- Symbols		6
Table 2 -- Reference values for the bound water content of dry (i.e. dried) hardened cement paste ...		8
Table 3 -- Reference values for partial factors and combination factors		15
Table 4 -- Partial factors for determining the design resistance at ultimate limit state (normal-weight concrete up to C50/60, high-ductility reinforcing steel)		16
Table 5 -- Damping of building elements, as a percentage of critical damping		19
Table 6 -- Maximum dynamic load factors		20

Table 7 -- Coefficients c_d for requirement categories A1, A2 and A322
Table A.1 -- Pressure ordinates as a function of impact angle (p from Figure A.3)29
Table A.2 -- Dynamic pressure q as a function of p_2 30