

DIN EN 14186:2008-02 (E)

Advanced technical ceramics - Mechanical properties of ceramic composites at room temperature - Determination of elastic properties by an ultrasonic technique

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	7
5	Significance and use	10
6	Apparatus	10
6.1	Ultrasonic tank with thermostatic control	10
6.2	Temperature measurement device	10
6.3	Test specimen holder	10
6.4	Transducers	11
6.5	Transducer holders	11
6.6	Pulse generator	11
6.7	Signal recording system	11
7	Test specimens	11
8	Test specimen preparation	11
9	Test procedure	12
9.1	Choice of frequency	12
9.2	Establishment of the test temperature	12
9.3	Reference test without test specimen	12
9.4	Measurement with the specimen	13
10	Calculation	14
10.1	Delay	14
10.2	Calculation of the propagation velocities	14
10.3	Calculation of the refracted angle r	14
10.4	Identification of the elastic constants, C_{ij}	14
10.5	Back calculation of the phase velocities	18
10.6	Polar plots of the velocity curves	18
10.7	Calculation of the quadratic deviation	18
10.8	Calculation of the engineering constants	18
11	Test validity	19
11.1	Measurements	19
11.2	Criterion of validity for the reliability of the C_{ij} components	19
12	Test report	19
Annex A (informative)	Example of a presentation of the results for a material with orthotropic symmetry	21
A.1	Velocity curves	21

A.2	Stiffness matrix with stiffness components	22
A.3	Engineering constants	23
	Bibliography	24