

# ISO 18213-6:2008-03 (E)

## Nuclear fuel technology - Tank calibration and volume determination for nuclear materials accountancy - Part 6: Accurate in-tank determination of liquid density in accountancy tanks equipped with dip tubes

---

| <b>Contents</b>           |   | <b>Page</b> |
|---------------------------|---|-------------|
| Foreword .....            |   | iv          |
| Introduction .....        |   | v           |
| <b>1</b>                  | <b>Scope .....</b>  | <b>1</b>    |
| <b>2</b>                  | <b>Normative references .....</b>                               | <b>1</b>    |
| <b>3</b>                  | <b>Physical principles involved .....</b>                       | <b>2</b>    |
| <b>4</b>                  | <b>Required data .....</b>                                      | <b>4</b>    |
| <b>5</b>                  | <b>Equipment required .....</b>                                 | <b>4</b>    |
| <b>6</b>                  | <b>Operating procedures .....</b>                               | <b>5</b>    |
| <b>7</b>                  | <b>Calculation of probe separation and liquid density .....</b> | <b>5</b>    |
| <b>7.1</b>                | <b>General .....</b>  | <b>5</b>    |
| <b>7.2</b>                | <b>Case 1: Fast bubbling rate .....</b>                         | <b>5</b>    |
| <b>7.3</b>                | <b>Case 2: Slow bubbling rate .....</b>                         | <b>8</b>    |
| <b>8</b>                  | <b>Uncertainty estimation .....</b>                             | <b>10</b>   |
| <b>8.1</b>                | <b>Density .....</b>  | <b>10</b>   |
| <b>8.2</b>                | <b>Local acceleration due to gravity .....</b>                  | <b>11</b>   |
| <b>8.3</b>                | <b>Changes in reference conditions .....</b>                    | <b>11</b>   |
| <b>Bibliography .....</b> |   | <b>12</b>   |