DIN EN ISO 6892-1:2009-12 (E)

Metallic materials - Tensile testing - Part 1: Method of test at room temperature (ISO 6892-1:2009)

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Terms and symbols 12

5 Principle 13

6 Test piece 13

7 Determination of original cross-sectional area 15

8 Marking the original gauge length 15

9 Accuracy of testing apparatus 16

10 Conditions of testing 16

11 Determination of the upper yield strength 20

12 Determination of the lower yield strength 20

13 Determination of proof strength, plastic extension 20

14 Determination of proof strength, total extension 21

15 Method of verification of permanent set strength 21

16 Determination of the percentage yield point extension 21

17 Determination of the percentage plastic extension at maximum force 21

18 Determination of the percentage total extension at maximum force 22

19 Determination of the percentage total extension at fracture 22

20 Determination of percentage elongation after fracture 23

21 Determination of percentage reduction of area 23

22 Test report 24

23 Measurement uncertainty 24

Annex A (informative) Recommendations concerning the use of computer-controlled tensile testing machines 38

Annex B (normative) Types of test pieces to be used for thin products: sheets, strips and flats between 0,1 mm and 3 mm thick 44

Annex C (normative) Types of test pieces to be used for wire, bars and sections with a diameter or thickness of less than 4 mm 47

Annex D (normative) Types of test pieces to be used for sheets and flats of thickness equal to or greater than 3 mm, and wire, bars and sections of diameter or thickness equal to or greater than 4 mm 48

Annex E (normative) Types of test pieces to be used for tubes 52

Annex F (informative) Estimation of the crosshead separation rate in consideration of the stiffness (or compliance) of the testing machine 54

Annex G (informative) Measuring the percentage elongation after fracture if the specified value is less than 5 % 55

Annex H (informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length 56

Annex I (informative) Determination of the percentage plastic elongation without necking, Awn, for long products such as bars, wire and rods 58

Annex J (informative) Estimation of the uncertainty of measurement 59

Annex K (informative) Precision of tensile testing -- Results from interlaboratory programmes 63

Bibliography 68