

ISO 28763:2008-10 (E)

Vitreous and porcelain enamels - Regenerative, enamelled and packed panels for air-gas and gas-gas heat exchangers - Specifications

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Steel substrates	3
4.1	Delivery	3
4.2	Analysis	3
4.3	Hydrogen permeability	3
4.4	Fish scale test	3
4.5	Pickling speed	4
5	Enamel frit(s)	4
5.1	Delivery	4
5.2	Coefficient of expansion	4
5.3	Fusion flow	4
5.4	Boiling water vapour resistance	4
5.5	Acid resistance	4
5.6	Thermal shock resistance	5
5.7	Adherence	5
6	Characteristics of the enamel coating	5
6.1	Adherence	5
6.2	Thickness	5
6.3	Thermal shock resistance	6
6.4	Fundamental defects	6
6.5	Open defects	7
6.6	Edge covering of gas-gas heaters	7
6.7	Boiling sulphuric acid resistance	7
6.8	Rework	7
7	Characteristics after packing	8
7.1	Packing pressure	8
7.2	Visual examination	8
7.3	Edge covering of gas-gas heaters	8
8	Documentation	8
Annex A (normative)	Method for determining thermal shock resistance of vitreous or porcelain enamel coatings	10