DIN 25475-2:2009-05 (E)

Nuclear facilities - Operational monitoring - Part 2: Vibration monitoring for earl y detection of changes in the vibrational behavior of the primary coolant circuit in pressurized water reactors

Contents

Page

Foreword 3

1 Scope 3

2 Normative references 3

3 Terms and definitions 4

4 Description of the monitoring technology 4

5 Requirements of the vibration monitoring system 7
5.1 Basic structure and interpretation criteria 7
5.2 Data acquisition 9
5.2.1 General 9
5.2.2 Selecting locations and installing the transducers and cables 9
5.2.3 Example of a data acquisition 12
5.3 Signal conditioning 18
5.4 Signal analysis 19
5.5 Signal presentation 19
5.5.1 Display unit 19
5.5.2 Recording 19
5.6 Calibration 19
5.6.1 General 19
5.6.2 Calibration unit 20

6 Commissioning 20
6.1 General 20
6.2 System checks 20
6.3 Measurements during commissioning of the reactor 20

7 Performance of monitoring 21
7.1 General 21
7.2 Prerequisites 21
7.3 Measurements 22
7.3.1 General 22
7.3.2 Reference measurements 22
7.3.3 Operational measurements 23
7.3.4 Identification 23
7.4 Monitoring 23
7.4.1 Selecting a comparative measurement 23
7.4.2 Determination and evaluation of changes 24
7.5 Test of the monitoring system 28
7.5.1 General 28
7.5.2 Test during fuel outage of the plant 29
7.5.3 Test during operation of the reactor 29

8 Documentation 29

Annex A (informative) Vibration monitoring, Example 1 31

A.1 General 31
A.2 Monitoring of the components of the primary circuit and reactor pressure vessel internals 31
A.3 Frequency-selective monitoring of the shaft vibrations of the main coolant pumps 33

Annex B (informative) Vibration monitoring, Example 2 43

B.1 Monitoring the components of the primary circuit and reactor pressure vessel internals . 43
B.2 Frequency-selective monitoring of shaft vibrations in the main coolant pumps 45

Annex C (informative) Example of signal trends of a fractured shaft 56

Bibliography 58