

# ISO 2439:2008-12 (E)

## Flexible cellular polymeric materials - Determination of hardness (indentation technique)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Principle .....</b>	<b>2</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>6</b>	<b>Test pieces .....</b>	<b>3</b>
<b>6.1</b>	<b>Shape and dimensions .....</b>	<b>3</b>
<b>6.2</b>	<b>Samples showing orientation .....</b>	<b>3</b>
<b>6.3</b>	<b>Conditioning .....</b>	<b>3</b>
<b>7</b>	<b>Procedure .....</b>	<b>3</b>
<b>7.1</b>	<b>General .....</b>	<b>3</b>
<b>7.2</b>	<b>Preliminary indentation for Methods A, B and C .....</b>	<b>4</b>
<b>7.3</b>	<b>Method A -- Determination of the 40 %/30 s indentation hardness index .....</b>	<b>4</b>
<b>7.4</b>	<b>Method B -- Determination of the 25 %-40 %-65 %/30 s indentation hardness characteristics .....</b>	<b>4</b>
<b>7.5</b>	<b>Method C -- Determination of the 40 % indentation hardness check .....</b>	<b>5</b>
<b>7.6</b>	<b>Method D -- Determination of the 25 %/20 s low indentation hardness index .....</b>	<b>5</b>
<b>7.7</b>	<b>Method E -- Determination of the compressive deflection coefficient and hysteresis loss rate .....</b>	<b>5</b>
<b>8</b>	<b>Repeat tests .....</b>	<b>7</b>
<b>9</b>	<b>Test report .....</b>	<b>7</b>
<b>Annex A (informative) Test method parameters and typical graphs .....</b>		<b>8</b>
<b>Annex B (informative) Precision of Method E .....</b>		<b>12</b>
<b>Bibliography .....</b>		<b>14</b>