

DIN 53504:2009-10 (E)

Testing of rubber - Determination of tensile strength at break, tensile stress at yield, elongation at break and stress values in a tensile test

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Designation | 6 |
| 5 | Apparatus | 6 |
| 5.1 | Instrument for measuring the thickness of test pieces | 6 |
| 5.2 | Instruments for determining the initial cross-section of rings | 6 |
| 5.3 | Tensile testing machine | 7 |
| 6 | Test pieces | 8 |
| 6.1 | Shape of test pieces | 8 |
| 6.2 | Preparation of test pieces | 10 |
| 6.3 | Number of test pieces | 11 |
| 6.4 | Reference marks | 11 |
| 7 | Procedure | 11 |
| 7.1 | General | 11 |
| 7.2 | Measurement of test pieces | 12 |
| 7.3 | Fitting of the dumb-bell test piece | 12 |
| 7.4 | Tensile testing | 13 |
| 7.5 | Determination of stress/strain properties | 14 |
| 8 | Evaluation | 14 |
| 8.1 | Tensile strength of break | 14 |
| 8.2 | Tensile stress at yield | 15 |
| 8.3 | Elongation at break | 15 |
| 8.4 | Stress | 16 |
| 8.5 | General | 16 |
| 9 | Test report | 16 |
| 10 | Precision | 17 |
| 10.1 | General | 17 |
| 10.2 | Repeatability limit | 17 |
| 10.3 | Reproducibility limit | 17 |
| Bibliography | | 18 |