

DIN EN 12668-2:2010-06 (E)

Non-destructive testing - Characterization and verification of ultrasonic examination equipment - Part 2: Probes

Contents		Page
Foreword		4
1	Scope	5
2	Normative references	5
3	Terms and definitions	5
4	General requirements for compliance	7
5	Technical specification for probes	7
6	Test equipment	11
6.1	Electronic equipment	11
6.2	Test blocks and other equipment	11
7	Performance requirements for probes	14
7.1	Physical aspects	14
7.1.1	Method	14
7.1.2	Acceptance criterion	14
7.2	Radio frequency pulse shape	14
7.2.1	Method	14
7.2.2	Acceptance criterion	14
7.3	Pulse spectrum and bandwidth	14
7.3.1	Method	14
7.3.2	Acceptance criteria	15
7.4	Relative pulse-echo sensitivity	15
7.4.1	Method	15
7.4.2	Acceptance criterion	15
7.5	Distance-amplitude curve	15
7.5.1	Method	15
7.5.2	Acceptance criterion	16
7.6	Electrical impedance	17
7.6.1	Method	17
7.6.2	Acceptance criteria	17
7.7	Beam parameters for immersion probes	17
7.7.1	General	17
7.7.2	Beam profile - measurements performed directly on the beam	18
7.7.3	Beam profile - measurements made using an automated scanning system	20
7.8	Beam parameters for contact, straight-beam, single transducer probes	21
7.8.1	General	21
7.8.2	Beam divergence and side lobes	22
7.8.3	Squint angle and offset	23
7.8.4	Focal distance (near field length)	23
7.8.5	Focal width	24
7.8.6	Focal length	24
7.9	Beam parameters for contact angle-beam single transducer probes	25
7.9.1	General	25
7.9.2	Index point	25
7.9.3	Beam angle and beam divergence	25
7.9.4	Squint angle and offset	26

7.9.5	Focal distance (near field length)	27
7.9.6	Focal width	28
7.9.7	Focal length	28
7.10	Beam parameters for contact, straight beam, dual-element probes	29
7.10.1	General	29
7.10.2	Cross talk	29
7.10.3	Distance to sensitivity maximum (focal distance)	29
7.10.4	Axial sensitivity range (focal length)	29
7.10.5	Lateral sensitivity range (focal width)	30
7.11	Beam parameters for contact angle beam, dual-element probes	30
7.11.1	General	30
7.11.2	Cross talk	31
7.11.3	Index point	31
7.11.4	Beam angle and profiles	31
7.11.5	Distance to sensitivity maximum (focal distance)	32
7.11.6	Axial sensitivity range (focal length)	32
7.11.7	Lateral sensitivity range (focal width)	32
Annex A (normative) Calculation of near field length of non-focusing probes		45
A.1	General	45
A.2	Straight beam probes	45
A.3	Angle beam probes	46
Annex B (informative) Calibration block for angle-beam probes		48
Bibliography		52