

ISO 1456:2009-08 (E)

Metallic and other inorganic coatings - Electrodeposited coatings of nickel, nickel plus chromium, copper plus nickel and of copper plus nickel plus chromium

| Contents | | Page |
|------------------------------------------------------------------------------------------|----------------------------------------------------------------------|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 2 |
| 4 | Information to be supplied by the purchaser to the processor | 3 |
| 4.1 | Essential information | 3 |
| 4.2 | Additional information | 3 |
| 5 | Designation | 4 |
| 5.1 | General | 4 |
| 5.2 | Designation specifications | 4 |
| 5.3 | Service-condition number | 5 |
| 5.4 | Type of copper coating | 13 |
| 5.5 | Types of nickel coating | 13 |
| 5.6 | Types and thicknesses of chromium | 14 |
| 6 | Requirements | 14 |
| 6.1 | Appearance | 14 |
| 6.2 | Coating thickness | 15 |
| 6.3 | Double- and triple-layer nickel coatings | 15 |
| 6.4 | Adhesion | 15 |
| 6.5 | Corrosion resistance in CASS, Corrodokote and salt spray tests | 15 |
| 6.6 | STEP test requirements | 15 |
| 6.7 | Ductility | 16 |
| 6.8 | Stress-relief heat treatments before coating | 16 |
| 6.9 | Hydrogen-embrittlement-relief treatment | 16 |
| 6.10 | Sampling | 16 |
| Annex A (informative) Determination of cracks and pores in chromium coatings | | 17 |
| Annex B (normative) Methods of test for the determination of thickness | | 20 |
| Annex C (normative) Ductility test | | 22 |
| Annex D (normative) Determination of the sulfur content of electrodeposited nickel | | 23 |
| Annex E (informative) Step test method | | 24 |
| Bibliography | | 25 |