

DIN EN ISO 14713-2:2010-05 (E)

Zinc coatings - Guidelines and recommendations for the protection against corrosion of iron and steel in structures - Part 2: Hot dip galvanizing (ISO 14713-2:2009)

| Contents | | Page |
|---|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 5 |
| 4 | Design for hot dip galvanizing | 5 |
| 4.1 | General | 5 |
| 4.2 | Surface preparation | 5 |
| 4.3 | Procedures related to design considerations | 6 |
| 4.4 | Design features | 6 |
| 4.5 | Tolerances | 6 |
| 5 | Design for storage and transport | 7 |
| 6 | Effect of article condition on quality of hot dip galvanizing | 7 |
| 6.1 | General | 7 |
| 6.2 | Surface condition | 9 |
| 6.3 | Influence of steel surface roughness on the hot dip galvanized coating thickness | 9 |
| 6.4 | Influence of thermal cutting processes | 9 |
| 6.5 | Effect of internal stresses in the basis steel | 9 |
| 6.6 | Large objects or thick steels | 10 |
| 6.7 | Hot dip galvanizing practice | 10 |
| 7 | Effect of hot dip galvanizing process on the article | 11 |
| 7.1 | Dimensional tolerances on mating thread | 11 |
| 7.2 | Effect of process heat | 11 |
| 8 | After-treatments | 11 |
| Annex A (informative) Preferred designs of articles for hot dip galvanizing | | 12 |
| Bibliography | | 21 |