

ISO 6892-1:2009-08 (E)

Metallic materials - Tensile testing - Part 1: Method of test at room temperature

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Terms and symbols	7
5	Principle	8
6	Test piece	8
7	Determination of original cross-sectional area	10
8	Marking the original gauge length	10
9	Accuracy of testing apparatus	11
10	Conditions of testing	11
11	Determination of the upper yield strength	15
12	Determination of the lower yield strength	15
13	Determination of proof strength, plastic extension	15
14	Determination of proof strength, total extension	16
15	Method of verification of permanent set strength	16
16	Determination of the percentage yield point extension	16
17	Determination of the percentage plastic extension at maximum force	16
18	Determination of the percentage total extension at maximum force	17
19	Determination of the percentage total extension at fracture	17
20	Determination of percentage elongation after fracture	18
21	Determination of percentage reduction of area	18
22	Test report	19
23	Measurement uncertainty	19
Annex A (informative) Recommendations concerning the use of computer-controlled tensile testing machines		33
Annex B (normative) Types of test pieces to be used for thin products: sheets, strips and flats between 0,1 mm and 3 mm thick		39
Annex C (normative) Types of test pieces to be used for wire, bars and sections with a diameter or thickness of less than 4 mm		42
Annex D (normative) Types of test pieces to be used for sheets and flats of thickness equal to or greater than 3 mm, and wire, bars and sections of diameter or thickness equal to or greater than 4 mm		43
Annex E (normative) Types of test pieces to be used for tubes		47

Annex F (informative) Estimation of the crosshead separation rate in consideration of the stiffness (or compliance) of the testing machine	49
Annex G (informative) Measuring the percentage elongation after fracture if the specified value is less than 5 %	50
Annex H (informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length	51
Annex I (informative) Determination of the percentage plastic elongation without necking, A_wn, for long products such as bars, wire and rods	53
Annex J (informative) Estimation of the uncertainty of measurement	54
Annex K (informative) Precision of tensile testing -- Results from interlaboratory programmes	58
Bibliography	63