

DIN EN 1071-13:2010-07 (E)

Advanced technical ceramics - Methods of test for ceramic coatings - Part 13: Determination of wear rate by the pin-on-disk method

Contents		Page
Foreword		3
Introduction		4
1 Scope		5
2 Normative references		5
3 Terms and definitions		5
4 Significance and use		6
5 Principle		6
6 Apparatus		6
6.1 Pin-on-disk method testing apparatus		6
6.2 Test apparatus design requirements		7
6.3 Instruments for determining the volume loss		8
6.4 Operating environment		8
7 Preparation of test pieces		8
7.1 Substrate material and preparation		8
7.2 Coating deposition		9
7.3 Post-coating preparation		9
7.4 Cleaning		10
8 Testing procedure		10
8.1 Preliminary setup		10
8.2 Producing the wear track and scar		11
8.3 Evaluation of wear and measurement of wear scars		11
8.4 Calculation of test results		14
9 Repeatability and limits		15
10 Report		16
Annex A (informative) Methods for the determination of coating properties likely to be relevant to coating performance in a pin-on-disk wear test		18
A.1 Relevant properties		18
A.2 Phase composition and preferred orientation		18
A.3 Residual stress		18
A.4 Hardness		18
Annex B (informative) Determination of volume loss from the pin using profilometry		19
Annex C (informative) Determination of wear of coated disk by ball crater technique		20
Bibliography		23