

DIN EN ISO 15653:2010-09 (E)

Metallic materials - Method of test for the determination of quasistatic fracture toughness of welds (ISO 15653:2010)

Contents		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Symbols and units	6
5	Principle	6
6	Choice of specimen design, specimen orientation and notch location	7
6.1	Classification of target area for notching	7
6.2	Specimen design	7
6.3	Specimen and crack plane orientation	7
7	Pre-machining metallography	11
7.1	Microstructural assessment of macrosections	11
7.2	Additional requirements for heat-affected zone tests	12
8	Machining	12
8.1	Tolerances on specimen dimensions	12
8.2	Notch placement for through-thickness notched specimens	13
8.3	Notch placement for surface-notched specimens	13
8.4	Notch machining	13
9	Specimen preparation	18
9.1	Fatigue precracking	18
9.2	Side grooving	18
10	Test apparatus, requirements and test procedure	18
11	Post-test metallography	18
11.1	General	18
11.2	Through-thickness notched specimens	19
11.3	Surface-notched specimens	19
11.4	Assessment of pop-in	19
12	Post-test analysis	22
12.1	Choice of tensile properties	22
12.2	K _{Ic}	23
12.3	and J	23
12.4	Qualification requirements	23
13	Test report	27
Annex A (informative) Examples of notch locations		28
Annex B (informative) Examples of pre-test and post-test metallography		30

Annex C (normative) Residual-stress modification and precracking technique	32
Annex D (normative) Assessment of pop-in	34
Annex E (informative) Shallow-notched specimen testing	40
Bibliography	44