

DIN EN 1007-5:2010-06 (E)

Advanced technical ceramics - Ceramic composites - Methods of test for reinforcements - Part 5: Determination of distribution of tensile strength and of tensile strain to failure of filaments within a multifilament tow at ambient temperature

Contents		Page
page	Foreword	3
1	Scope	4
2	Normative references	4
3	Terms and definitions	4
4	Principle	6
5	Significance and use	6
6	Apparatus	6
6.1	Tensile testing equipment	6
6.2	Load train	6
6.3	Data recording	7
7	Test specimens	7
7.1	General	7
7.2	Window type specimen	7
7.3	Cylindrical end type specimen	8
8	Test specimen preparation	8
8.1	General	8
8.2	Window type specimen	8
8.3	Cylindrical end type specimen	9
8.4	Number of test specimens	9
8.5	Determination of the initial cross sectional area	9
8.6	Determination of the gauge length	10
9	Testing technique	10
9.1	Test specimen mounting	10
9.2	Selection of strain rate	10
9.3	Measurement	11
9.4	Determination of load train compliance	11
9.5	Test validity	11
10	Calculation of results	11
10.1	Calculation of the parasitic load train compliances	11
10.2	Determination of true origin	12
10.3	Construction of envelope curve and determination of instantaneous compliance $C_{t,j}$	12
10.4	Probability of filament rupture	13
10.5	Distribution of filament strain	13
10.5.1	Calculation of filament strain	13
10.5.2	Distribution of filament strain	13
10.6	Distribution of filament strength	14
10.6.1	Initial cross sectional area	14
10.6.2	Elastic modulus (Young's modulus) of the tow	14
10.6.3	Calculation of filament strength and filament strength distribution	15

10.7	Average filament rupture strain and average filament rupture strength	15
10.8	Overall average filament rupture strain and overall average filament rupture strength	15
10.9	Calculation of tow strength	16
11	Test report	16
	Bibliography	18