

ISO 15653:2010-04 (E)

Metallic materials - Method of test for the determination of quasistatic fracture toughness of welds

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and units	3
5	Principle	3
6	Choice of specimen design, specimen orientation and notch location	4
6.1	Classification of target area for notching	4
6.2	Specimen design	4
6.3	Specimen and crack plane orientation	4
7	Pre-machining metallography	8
7.1	Microstructural assessment of macrosections	8
7.2	Additional requirements for heat-affected zone tests	9
8	Machining	9
8.1	Tolerances on specimen dimensions	9
8.2	Notch placement for through-thickness notched specimens	10
8.3	Notch placement for surface-notched specimens	10
8.4	Notch machining	10
9	Specimen preparation	15
9.1	Fatigue precracking	15
9.2	Side grooving	15
10	Test apparatus, requirements and test procedure	15
11	Post-test metallography	15
11.1	General	15
11.2	Through-thickness notched specimens	16
11.3	Surface-notched specimens	16
11.4	Assessment of pop-in	16
12	Post-test analysis	19
12.1	Choice of tensile properties	19
12.2	K _{Ic}	20
12.3	and J	20
12.4	Qualification requirements	20
13	Test report	24
Annex A (informative) Examples of notch locations		25
Annex B (informative) Examples of pre-test and post-test metallography		27

Annex C (normative) Residual-stress modification and precracking technique	29
Annex D (normative) Assessment of pop-in	31
Annex E (informative) Shallow-notched specimen testing	37
Bibliography	41