

# DIN EN 843-7:2010-11 (E)

## Advanced technical ceramics - Mechanical properties of monolithic ceramics at room temperature - Part 7: C-ring tests

---

| <b>Contents</b>                               |   | <b>Page</b> |
|---|---|-------------|
| Foreword .....                                |   | 3           |
| 1   | Scope .....                               | 4           |
| 2   | Normative references .....                | 4           |
| 3   | Definitions .....                         | 4           |
| 4   | Significance and use .....                | 4           |
| 5   | Principle .....                           | 5           |
| 5.1   | Method A: C-ring compression .....        | 5           |
| 5.2   | Method B: C-ring tension .....            | 5           |
| 6   | Apparatus .....                           | 6           |
| 6.1   | Cutting machine .....                     | 6           |
| 6.2   | Vernier callipers .....                   | 6           |
| 6.3   | Micrometer callipers .....                | 6           |
| 6.4   | Mechanical testing machine .....          | 7           |
| 6.5   | Interface material .....                  | 7           |
| 7   | Test pieces .....                         | 7           |
| 8   | Test procedure .....                      | 8           |
| 8.1   | Test-piece dimensions .....               | 8           |
| 8.2   | Mechanical testing .....                  | 8           |
| 9   | Calculation .....                         | 8           |
| 9.1   | Method A: C-ring compression .....        | 8           |
| 9.2   | Method B: C-ring tension test .....       | 9           |
| 9.3   | Mean and standard deviation .....         | 9           |
| 9.4   | Fractures away from the centre-line ..... | 9           |
| 10  | Interferences .....                       | 9           |
| 11  | Report .....                              | 10          |
| Annex A (informative) C-ring compliance ..... |   | 11          |
| Bibliography .....                            |   | 12          |