

DIN EN 15365:2010-12 (E)

Advanced technical ceramics - Mechanical properties of ceramic fibres at high temperature in a non-reactive environment - Determination of creep behaviour by the cold end method

| Contents | | Page |
|--------------------|--|-------------|
| Foreword | | 3 |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 | Principle | 7 |
| 5 | Significance and use | 8 |
| 6 | Apparatus | 8 |
| 6.1 | Test installations | 8 |
| 6.2 | Load train | 8 |
| 6.3 | Test chamber | 9 |
| 6.4 | Set-up for heating | 9 |
| 6.5 | Temperature measurement | 9 |
| 6.6 | Control of deformation | 9 |
| 6.7 | Data recording system | 9 |
| 6.8 | Determination of fibre cross sectional area | 9 |
| 7 | Test specimens | 9 |
| 7.1 | Test specimen preparation | 9 |
| 7.2 | Number of test specimens | 11 |
| 8 | Test procedures | 11 |
| 8.1 | Determination of the temperature profile in the furnace | 11 |
| 8.2 | Test set-up: Determination of the temperature profile and of the different lengths of each temperature zone in the furnace | 11 |
| 8.3 | Test set-up: Loading considerations | 12 |
| 8.4 | Test technique | 12 |
| 8.5 | Test validity | 14 |
| 9 | Calculation of results | 14 |
| 9.1 | Creep stress | 14 |
| 9.2 | Creep strain at time t | 14 |
| 10 | Test report | 15 |
| Bibliography | | 17 |