

# ISO 26945:2011-02 (E)

## Metallic and other inorganic coatings - Electrodeposited coatings of tin-cobalt alloy

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>2</b>
<b>4</b>	<b>Essential information to be supplied by the purchaser to the processor .....</b>	<b>2</b>
<b>5</b>	<b>Designation .....</b>	<b>3</b>
<b>5.1</b>	<b>General .....</b>	<b>3</b>
<b>5.2</b>	<b>Designation specification .....</b>	<b>3</b>
<b>5.3</b>	<b>Basis metal .....</b>	<b>3</b>
<b>5.4</b>	<b>Designation of heat treatment requirements .....</b>	<b>4</b>
<b>5.5</b>	<b>Examples .....</b>	<b>4</b>
<b>6</b>	<b>Requirements .....</b>	<b>4</b>
<b>6.1</b>	<b>Basis material .....</b>	<b>4</b>
<b>6.2</b>	<b>Appearance .....</b>	<b>5</b>
<b>6.3</b>	<b>Undercoats .....</b>	<b>5</b>
<b>6.4</b>	<b>Thickness .....</b>	<b>5</b>
<b>6.5</b>	<b>Adhesion .....</b>	<b>6</b>
<b>6.6</b>	<b>Quality-evaluation test of tin-cobalt alloy coatings .....</b>	<b>6</b>
<b>6.7</b>	<b>Stress-relief heat treatment prior to electroplating .....</b>	<b>7</b>
<b>6.8</b>	<b>Hydrogen-embrittlement-relief heat treatment after electroplating .....</b>	<b>7</b>
<b>7</b>	<b>Sampling .....</b>	<b>7</b>
<b>Annex A (normative) Methods of measuring the thickness of tin-cobalt alloy coatings .....</b>		<b>8</b>
<b>Bibliography .....</b>		<b>10</b>