

ISO/TS 11366:2011-03 (E)

Petroleum and related products - Guidance for in-servicing of lubricating oils for steam, gas and combined-cycle turbines

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Description of turbine oils	1
4	Factors affecting the service life	2
4.1	General	2
4.2	Oil system design	3
4.3	Conditions of the oil system at start-up	3
4.4	Original oil quality	3
4.5	System operating temperature	3
4.6	Contamination rates and provisions for purification	4
4.7	Oil make-up rates	4
5	Deterioration of turbine oils in service	4
5.1	General	4
5.2	Viscosity	4
5.3	Oxidation stability	4
5.4	Solid particles	5
5.5	Sludge	5
5.6	Antirust properties	5
5.7	Water separability	6
5.8	Foaming and air-release characteristics	6
5.9	Total acid number	7
6	Recommended tests and interpretation	7
6.1	Appearance and odour	7
6.2	Colour	7
6.3	Total acid number	7
6.4	Sludge and deposits	7
6.5	Particle counting	8
6.6	Kinematic viscosity	8
6.7	Remaining oxidation stability	8
6.8	Water content	9
6.9	Rust prevention characteristics	9
6.10	Water separability	9
6.11	Foaming characteristics	9
6.12	Air-release value	10
6.13	Flash point	10
7	Sampling	10
7.1	General	10
7.2	Sampling point	10
7.3	Sampling line	11
7.4	Containers	11
7.5	Samples marking	11

8	Examination of new oil	12
8.1	General	12
8.2	Sampling of new oil deliveries	12
8.3	Examination of new oil deliveries	13
8.4	Testing schedules	13
9	Examination of oils in service	15
9.1	Testing procedures	15
9.2	Frequency of the testing	18
	Bibliography	20