

# ISO 11311:2011-07 (E)

## Nuclear criticality safety - Critical values for homogeneous plutonium-uranium oxide fuel mixtures outside of reactors

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Reference systems concerned by this International Standard .....</b>	<b>1</b>
4.1	Reference fissile media .....	1
4.2	Moderation conditions .....	3
4.3	Geometrical models .....	4
4.4	Reflecting conditions .....	4
<b>5</b>	<b>Critical values .....</b>	<b>4</b>
5.1	Presentation of the results .....	4
5.2	Requirements .....	4
<b>6</b>	<b>Subcritical limits and margin of safety .....</b>	<b>5</b>
Annex A (informative) Reference fissile media .....		6
Annex B (informative) Criticality schemes used for the calculations .....		7
Annex C (normative) Critical dimensions for a water reflection of 30 cm .....		9
Annex D (normative) Critical dimensions for a water reflection of 2,5 cm .....		10
Annex E (normative) Critical parameters for a water reflection of 30 cm .....		11
Annex F (normative) Critical parameters for a water reflection of 2,5 cm .....		12
Bibliography .....		13