ISO 13067:2011-11 (E)

Microbeam analysis - Electron backscatter diffraction - Measurement of average grain size

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 1
3.1 Terminology associated with EBSD measurement of grain size 1
3.2 Terminology associated with grains and grain boundaries determined via EBSD 3
3.3 Terminology associated within grain size measurement 4
3.4 Terminology associated with data correction and uncertainty of EBSD maps 5

4 Acquiring a map by EBSD for grain size measurement 5
4.1 Hardware requirements 5
4.2 Software requirements 6

5 Acquiring the map for grain sizing by EBSD 6
5.1 Specimen preparation 6
5.2 Defining specimen axes 6
5.3 Stage positioning and calibration 6
5.4 Linear calibration 6
5.5 Preliminary examination 7
5.6 Choice of step size 7
5.7 Determination of the level of angular accuracy needed[7][8] 7
5.8 Choice of areas to be mapped and map size 9
5.9 Considerations when examining plastically deformed materials 9

6 Analytical procedure 10
6.1 Definition of boundaries 10
6.2 Post-acquisition treatment of raw data 11
6.3 Data-cleaning steps 11
6.4 Measurement of grain size 14
6.5 Representation of data 14

7 Measurement uncertainty 15

8 Reporting of analysis results 15

Annex A (informative) Grain size measurement 16

Bibliography 18