

ISO 7743:2011-11 (E)

Rubber, vulcanized or thermoplastic - Determination of compression stress-strain properties

| Contents | | Page |
|--|--|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 2 |
| 3 | Terms and definitions | 2 |
| 4 | Principle | 2 |
| 5 | Apparatus and materials | 2 |
| 6 | Calibration | 3 |
| 7 | Test pieces | 3 |
| 8 | Number of test pieces | 4 |
| 9 | Time-lapse between vulcanization and testing | 4 |
| 10 | Conditioning | 4 |
| 11 | Temperature of test | 5 |
| 12 | Procedure | 5 |
| 12.1 | Measurement of test pieces | 5 |
| 12.2 | Determination of stress-strain properties | 5 |
| 13 | Expression of results | 6 |
| 13.1 | For methods A, B and C | 6 |
| 13.2 | For method D | 7 |
| 14 | Test report | 8 |
| 15 | Precision for methods A and D | 8 |
| Annex A (informative) Influence of test piece geometry | | 9 |
| Annex B (informative) Extrapolation of results to non-standard test pieces | | 13 |
| Annex C (normative) Calibration schedule | | 16 |
| Annex D (informative) Precision for methods A and D | | 18 |
| Bibliography | | 21 |