

ISO 16827:2012-04 (E)

Non-destructive testing - Ultrasonic testing - Characterization and sizing of discontinuities

Contents		Page
Foreword		v
1	Scope	1
2	Normative references	1
3	Principles of characterization of discontinuities	1
3.1	General	1
3.2	Requirements for surface condition	2
4	Pulse echo techniques	2
4.1	General	2
4.2	Location of discontinuity	2
4.3	Orientation of discontinuity	2
4.4	Assessment of multiple indications	3
4.5	Shape of discontinuity	3
4.5.1	Simple classification	3
4.5.2	Detailed classification of shape	4
4.6	Maximum echo height of indication	4
4.7	Size of discontinuity	4
4.7.1	General	4
4.7.2	Maximum echo height techniques	4
4.7.3	Probe movement sizing techniques	5
4.7.4	Selection of sizing techniques	5
4.7.5	Sizing techniques with focussing ultrasonic probes	6
4.7.6	Use of mathematical algorithms for sizing	6
4.7.7	Special sizing techniques	6
5	Transmission technique	7
5.1	General	7
5.2	Location of discontinuity	7
5.3	Evaluation of multiple discontinuities	7
5.4	Reduction of signal amplitude	8
5.5	Sizing of discontinuity	8
Annex A (normative) Analysis of multiple indications		12
A.1	Lateral characterisation	12
A.2	Transverse (Through-thickness) characterisation	12
A.3	Shadow technique	12
Annex B (normative) Techniques for the classification of discontinuity shape		14
B.1	Simple classification	14
B.1.1	General	14
B.1.2	Reconstruction technique	14
B.1.3	Echo envelope technique	14
B.2	Detailed classification	14
B.2.1	General	14
B.2.2	Echodynamic pattern technique	15
B.2.3	Directional reflectivity	17

B.3	Combination of data	17
Annex C (informative) Maximum echo height sizing technique		25
C.1	Distance-gain-size (DGS) technique	25
C.1.1	Principle	25
C.1.2	Applications and limitations	25
C.2	Distance-amplitude-correction (DAC) curve technique	25
C.2.1	Principle	25
Introduction		vi
C.2.2	Applications and limitations	26
Annex D (normative) Probe movement sizing techniques		27
D.1	Fixed amplitude level techniques	27
D.1.1	Principle	27
D.1.2	Application and limitations	27
D.2	6 dB drop from maximum technique	27
D.2.1	Principle	27
D.2.2	Application and limitations	27
D.3	12 dB or 20 dB drop from maximum technique	28
D.3.1	Principle	28
D.3.2	Application and limitations	28
D.4	Drop to noise level technique	28
D.4.1	Principle	28
D.4.2	Application and limitations	28
D.5	6 dB drop tip location technique	29
D.5.1	Principle	29
D.5.2	Application and limitations	29
D.6	Beam axis tip location technique	29
D.6.1	Principle	29
D.6.2	Application and limitations	29
D.7	20 dB drop tip location technique	30
D.7.1	Principle	30
D.7.2	Application and limitations	30
Annex E (normative) Iterative sizing technique		39
E.1	Scope	39
E.2	Normal incidence testing	39
E.2.1	Principle	39
E.2.2	Adjustment of gain	39
E.2.3	Procedure	39
E.3	Oblique incidence testing	40
Annex F (normative) Mathematical algorithms for the estimation of the actual size of a discontinuity		45
F.1	Large planar discontinuities	45
F.2	Small planar discontinuities	46
F.3	Planar discontinuities in a cylindrical test object	48
Annex G (informative) Examples of special sizing techniques		50
G.1	Tip diffraction techniques	50
G.2	Synthetic aperture focussing technique (SAFT)	51