ISO 16828:2012-04 (E)

Non-destructive testing - Ultrasonic testing - Time-of-flight diffraction technique as a method for detection and sizing of discontinuitie s

Contents

Page

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, symbols and abbreviations 2
3.1 Terms and definitions 2
3.2 Abbreviations 2
3.3 Symbols 2

4 General 3
4.1 Principle of the technique 3
4.2 Requirements for surface condition and couplant 5
4.3 Materials and process type 5

5 Qualification of personnel 5

6 Equipment requirements 5
6.1 Ultrasonic equipment and display 5
6.2 Ultrasonic probes 6
6.3 Scanning mechanisms 7

7 Equipment set-up procedures 7
7.1 General 7
7.2 Probe choice and probe separation 8
7.2.1 Probe selection 8
7.2.2 Probe separation 9
7.3 Time window setting 9
7.4 Sensitivity setting 9
7.5 Scan resolution setting 10
7.6 Setting of scanning speed 10
7.7 Checking system performance 10

8 Interpretation and analysis of data 10
8.1 Basic analysis of discontinuities 10
8.1.1 General 10
8.1.2 Characterisation of discontinuities 10
8.1.3 Estimation of discontinuity position 11
8.1.4 Estimation of discontinuity length 11
8.1.5 Estimation of discontinuity depth and height 12
8.2 Detailed analysis of discontinuities 12
8.2.1 General 12
8.2.2 Additional scans 13
8.2.3 Additional algorithms 14

9 Detection and sizing in complex geometries 14

10 Limitations of the technique 14
10.1 General 14
10.2 Accuracy and resolution 15

10.2.1 General 15
10.2.2 Errors in the lateral position 15
10.2.3 Timing errors 15
10.2.4 Errors in sound velocity 15
10.2.5 Errors in probe centre separation 15
10.2.6 Spatial resolution 16
10.3 Dead zones 16

Foreword v

11 TOFD examination without data recording 16

12 Test procedure 17

13 Test report 17

Annex A (normative) Reference blocks 18

Bibliography 19