

# ISO 248-2:2012-05 (E)

## Rubber, raw - Determination of volatile-matter content - Part 2: Thermogravimetric methods using an automatic analyser with an infrared drying unit

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>1</b>
<b>4</b>	<b>Reagents .....</b>	<b>2</b>
<b>5</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5.1</b>	<b>Automatic analyser .....</b>	<b>2</b>
<b>6</b>	<b>Sampling and preparation of test portion .....</b>	<b>2</b>
<b>7</b>	<b>Procedure .....</b>	<b>2</b>
<b>7.1</b>	<b>General .....</b>	<b>2</b>
<b>7.2</b>	<b>Determination of end points for method A and method B .....</b>	<b>3</b>
<b>7.3</b>	<b>MethodA(pre-defineddryingtimemethod) .....</b>	<b>4</b>
<b>7.4</b>	<b>MethodB(inwhichdryingendswhenthemasslossratehasdecreasedtoapre-defined level)5</b>	<b>5</b>
	<b>7.5 Calculation of volatile-matter content .....</b>	<b>5</b>
<b>8</b>	<b>Precision .....</b>	<b>5</b>
<b>9</b>	<b>Test report .....</b>	<b>5</b>
<b>Annex A (informative) Examples of test conditions .....</b>		<b>7</b>
<b>Annex B (informative) Precision .....</b>		<b>8</b>
<b>Bibliography .....</b>		<b>10</b>