

# ISO 9227:2012-05 (E)

## Corrosion tests in artificial atmospheres - Salt spray tests

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Test solutions .....</b>	<b>2</b>
<b>3.1</b>	<b>Preparation of the sodium chloride solution .....</b>	<b>2</b>
<b>3.2</b>	<b>pH adjustment .....</b>	<b>2</b>
<b>3.3</b>	<b>Filtration .....</b>	<b>2</b>
<b>4</b>	<b>Apparatus .....</b>	<b>3</b>
<b>4.1</b>	<b>Component protection .....</b>	<b>3</b>
<b>4.2</b>	<b>Spray cabinet .....</b>	<b>3</b>
<b>4.3</b>	<b>Heater and temperature control .....</b>	<b>3</b>
<b>4.4</b>	<b>Spraying device .....</b>	<b>3</b>
<b>4.5</b>	<b>Collecting devices .....</b>	<b>4</b>
<b>4.6</b>	<b>Reuse .....</b>	<b>4</b>
<b>5</b>	<b>Method for evaluating cabinet corrosivity .....</b>	<b>4</b>
<b>5.1</b>	<b>General .....</b>	<b>4</b>
<b>5.2</b>	<b>NSS test .....</b>	<b>5</b>
<b>5.3</b>	<b>AASS test .....</b>	<b>6</b>
<b>5.4</b>	<b>CASS test .....</b>	<b>7</b>
<b>6</b>	<b>Test specimens .....</b>	<b>8</b>
<b>7</b>	<b>Arrangement of the test specimens .....</b>	<b>8</b>
<b>8</b>	<b>Operating conditions .....</b>	<b>9</b>
<b>9</b>	<b>Duration of tests .....</b>	<b>9</b>
<b>10</b>	<b>Treatment of specimens after test .....</b>	<b>10</b>
<b>11</b>	<b>Evaluation of results .....</b>	<b>10</b>
<b>12</b>	<b>Test report .....</b>	<b>10</b>
<b>Annex A (informative)</b>	<b>Schematic diagram of one possible design of spray cabinet with means for treating fog exhaust and drain .....</b>	<b>12</b>
<b>Annex B (informative)</b>	<b>Complementary method for evaluating cabinet corrosivity using zinc reference specimens .....</b>	<b>14</b>
<b>Annex C (normative)</b>	<b>Preparation of panels with organic coatings for testing .....</b>	<b>16</b>
<b>Annex D (normative)</b>	<b>Required supplementary information for testing test panels with organic coatings .....</b>	<b>17</b>
<b>Bibliography .....</b>		<b>18</b>