

# ISO 4965-1:2012-07 (E)

## Metallic materials - Dynamic force calibration for uniaxial fatigue testing - Part 1: Testing systems

---

Contents	Page
<b>Foreword .....</b>	<b>iv</b>
<b>Introduction .....</b>	<b>v</b>
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms,definitions,andsymbols .....</b>	<b>1</b>
<b>4 General requirements .....</b>	<b>3</b>
<b>4.1 Temperature .....</b>	<b>3</b>
<b>4.2 Dynamic testing system .....</b>	<b>3</b>
<b>5 Procedure .....</b>	<b>5</b>
<b>5.1 Initial checks .....</b>	<b>5</b>
<b>5.2 Calibration procedure .....</b>	<b>6</b>
<b>6 Calculation of results .....</b>	<b>7</b>
<b>6.1 Calculate DCD forces and measured force ranges .....</b>	<b>7</b>
<b>6.2 Replica test-piece -- Method A .....</b>	<b>8</b>
<b>6.3 Compliance envelope -- Method B .....</b>	<b>8</b>
<b>7 Report .....</b>	<b>9</b>
<b>7.1 General information .....</b>	<b>9</b>
<b>7.2 Results of dynamic calibration .....</b>	<b>10</b>
<b>7.3 Re-calibration .....</b>	<b>10</b>
<b>Annex A (normative) Guidance on re-calibration to be supplied to the user .....</b>	<b>11</b>
<b>Annex B (informative) Guidance on estimation of the bandwidth of the testing system instrumentation .....</b>	<b>12</b>
<b>Bibliography .....</b>	<b>13</b>