

DIN EN ISO 9513:2013-05 (E)

Metallic materials - Calibration of extensometer systems used in uniaxial testing (ISO 9513:2012 + Cor. 1:2013)

Contents	Page
Foreword	3
Introduction	4
1 Scope	5
2 Terms and definitions	5
3 Symbols and designations	5
4 Principle	6
5 Calibration equipment	6
5.1 Calibration apparatus	6
5.2 Calibration traceability	6
6 Pre-calibration inspection	6
6.1 Objective	6
6.2 Records of the inspection	7
6.3 Identification of extensometer system elements	7
7 Measurement of extensometer gauge length	7
7.1 Fixed gauge length extensometry	7
7.2 Variable gauge length extensometry	7
7.3 Non-contacting extensometry	8
7.4 Extensometer gauge lengths established using setting gauges	8
8 Calibration process	8
8.1 Environmental considerations	8
8.2 Position of the extensometer	8
8.3 Calibration increments	8
8.4 Calibration process	10
8.5 Determination of the characteristics of the extensometer system	10
9 Classification of the extensometer system	11
9.1 Input data	11
9.2 Analysis of the data	11
9.3 Classification criteria	11
9.4 Assessment of the results	11
10 Uncertainty determination	12
10.1 Uncertainty of the calibration	12
10.2 Uncertainty budget determination	12
11 Extensometer system calibration intervals	12
12 Calibration certificate	12
12.1 Mandatory information	12
12.2 Data presentation	13
Annex A (informative) Uncertainty of measurement	14
Annex B (informative) Calibration of the calibration apparatus	19
Annex C (informative) Example of a report of the calibration of calibration apparatus	21
Annex D (informative) Examples of extensometer system configurations	24
Annex E (informative) Laser extensometry	33
Annex F (informative) Video extensometry	41
Annex G (informative) Full field strain measurement video extensometry	45
Annex H (informative) Calibration of a cross-head measurement system	47
Bibliography	48