

ISO/TS 15029-2:2012-12 (E)

Petroleum and related products - Determination of spray ignition characteristics of fire-resistant fluids - Part 2: Spray test - Stabilized flame heat release method

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Reagents and materials	2
6	Apparatus	2
6.1	Test installation	2
6.2	Instrumentation	7
7	Sampling and sample preparation	9
8	Apparatus preparation	10
9	Procedure	10
9.1	Measurements at a propane flow rate of 0,13 Nm ³ /h	10
9.2	Measurements at a propane flow rate of 0,4 Nm ³ /h	11
9.3	Rejection of test data	11
9.4	Tabulation of measurements	12
9.5	Number of tests	12
10	Calculations	13
10.1	Ignitability factor	13
10.2	Flame length index	14
10.3	Smoke density	14
11	Expression of results	14
11.1	Individual results	14
11.2	Ranking system	14
12	Precision	15
13	Test report	15
Annex A (normative) Verification of propane pressure and flow rate		16
Annex B (normative) Verification of propane flame characteristics		17
Annex C (normative) Test apparatus calibration		22
Annex D (informative) Suggested fire-resistant classification scheme		24
Annex E (informative) Example pro-forma for test results		25
Bibliography		28

