

DIN EN 15280:2013-12 (E)

Evaluation of a.c. corrosion likelihood of buried pipelines applicable to cathodically protected pipelines

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Cathodic protection personnel competence | 8 |
| 5 | Assessment of the a.c. influence | 9 |
| 5.1 | General | 9 |
| 5.2 | Assessment of the level of interference | 9 |
| 6 | Evaluation of the likelihood of a.c. corrosion | 10 |
| 6.1 | Prerequisite | 10 |
| 6.1.1 | General | 10 |
| 6.1.2 | A.c. voltage on the structure | 10 |
| 6.2 | A.c. and d.c. current density | 11 |
| 6.2.1 | General | 11 |
| 6.2.2 | A.c. current density | 11 |
| 6.2.3 | High cathodic d.c. current density | 11 |
| 6.2.4 | Low cathodic d.c. current density | 11 |
| 6.2.5 | Current ratio "I _{a.c.} /I _{d.c.} " | 12 |
| 6.2.6 | Soil resistivity | 12 |
| 6.3 | Corrosion rate | 12 |
| 6.4 | Pipeline coatings | 12 |
| 6.5 | Evaluation of the metal loss | 12 |
| 7 | Acceptable interference levels | 12 |
| 8 | Measurement techniques | 13 |
| 8.1 | Measurements | 13 |
| 8.1.1 | General | 13 |
| 8.1.2 | Selection of test sites | 13 |
| 8.1.3 | Selection of measurement parameter | 14 |
| 8.1.4 | Sampling rate for the recording of interference levels | 14 |
| 8.1.5 | Accuracy of measuring equipment | 14 |
| 8.1.6 | Installation of coupons or probes to calculate current densities | 14 |
| 8.2 | D.c. potential measurements | 14 |
| 8.3 | A.c. voltage measurements | 15 |
| 8.4 | Measurements on coupons and probes | 15 |
| 8.4.1 | Installation of coupons or probes | 15 |
| 8.4.2 | Current measurements | 15 |
| 8.4.3 | Corrosion rate measurements | 16 |
| 8.5 | Pipeline metal loss techniques | 17 |
| 9 | Mitigation measures | 17 |
| 9.1 | General | 17 |
| 9.2 | Construction measures | 17 |
| 9.2.1 | Modification of bedding material | 17 |

| | | |
|--|--|----|
| 9.2.2 | Installation of isolating joints | 17 |
| 9.2.3 | Installation of mitigation wires | 17 |
| 9.2.4 | Optimisation of pipeline and/or powerline route | 18 |
| 9.2.5 | Power line or pipeline construction | 18 |
| 9.3 | Operation measures | 18 |
| 9.3.1 | Earthing | 18 |
| 9.3.2 | Adjustment of cathodic protection level | 19 |
| 9.3.3 | Repair of coating defects | 19 |
| 10 | Commissioning | 19 |
| 10.1 | Commissioning | 19 |
| 10.2 | Preliminary checking | 20 |
| 10.2.1 | General | 20 |
| 10.2.2 | Start up | 20 |
| 10.2.3 | Verification of effectiveness | 21 |
| 10.2.4 | Installation and commissioning documents | 21 |
| 11 | Monitoring and maintenance | 21 |
| Annex A (informative) Simplified description of the a.c. corrosion phenomenon | | 23 |
| A.1 | Cathodically protected pipeline | 23 |
| A.2 | Cathodically protected pipeline with a.c. voltage | 23 |
| A.2.1 | Description of the phenomena | 23 |
| A.2.2 | Reduction of the a.c. corrosion rate | 24 |
| Annex B (informative) Coupons and probes | | 25 |
| B.1 | Use and sizes of coupons and probes | 25 |
| B.1.1 | Use of coupons or probes | 25 |
| B.1.2 | Sizes of coupons or probes | 25 |
| B.2 | Installation of buried coupons and probes | 25 |
| B.2.1 | General | 25 |
| B.2.2 | Before installing the coupon or probe | 25 |
| B.2.3 | Installation of the buried coupon or probe | 26 |
| B.3 | ER probes principles | 27 |
| B.3.1 | Assessment of the corrosion using the electrical resistance (ER) probe technique | 27 |
| B.3.2 | ER probe application in the field | 29 |
| B.4 | Perforation probes | 29 |
| Annex C (informative) Coulometric oxidation | | 31 |
| Annex D (informative) Influence of soil characteristics on the a.c. corrosion process | | 32 |
| D.1 | Influence of electrical parameters | 32 |
| D.2 | Influence of the electrochemical process | 32 |
| D.3 | Influence of alkaline ions and cations | 32 |
| Annex E (informative) Other criteria that have been used in the presence of a.c. influence | | 33 |
| E.1 | General | 33 |
| E.2 | ON-potential approach | 33 |
| E.2.1 | General | 33 |
| E.2.2 | More negative (Eon) cathodic protection level | 33 |
| E.2.3 | Less negative (Eon) cathodic protection level | 33 |
| E.2.4 | Criteria | 34 |
| Annex F (informative) Parameters to take into account to choose a d.c. decoupling device | | 36 |
| F.1 | General aspects to be taken into account | 36 |
| F.2 | Electrical parameters | 36 |

Annex G (informative) Method to determine the reference electrode location to remote earth37
Bibliography38