

DIN EN ISO 13934-1:2013-08 (E)

Textiles - Tensile properties of fabrics - Part 1: Determination of maximum force and elongation at maximum force using the strip method (ISO 13934-1:2013)

| Contents | | Page |
|--|---|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Principle | 7 |
| 5 | Sampling | 8 |
| 6 | Apparatus | 8 |
| 6.1 | CRE machine | 8 |
| 7 | Atmosphere for conditioning and testing | 9 |
| 8 | Preparation of test specimen | 9 |
| 8.1 | General | 9 |
| 8.2 | Dimensions | 9 |
| 8.3 | Preparation of test specimens | 9 |
| 8.4 | Wet test specimens | 10 |
| 9 | Procedure | 10 |
| 9.1 | Gauge length | 10 |
| 9.2 | Rate of extension or elongation | 10 |
| 9.3 | Mounting of test specimens | 11 |
| 9.4 | Operation | 11 |
| 9.5 | Tests on wet test specimens | 12 |
| 10 | Calculation and expression of results | 12 |
| 11 | Test report | 12 |
| Annex A (informative) Suggested procedure for sampling | | 14 |
| Annex B (informative) Locations of test specimens cut from a laboratory sample | | 15 |
| Bibliography | | 16 |