

# DIN EN 31092:2013-09 (E)

Textiles - Physiological effects - Measurement of thermal and water-vapour resistance under steady-state conditions (sweating guarded-hotplate test) (ISO 11092:1993 + Amd.1:2012) (includes Amendment :2012)

---

## Contents

Page

Foreword.....	3
<b>[A1]</b> Foreword to EN 31092:1993/A1:2012.....	3
Introduction .....	4
<b>1</b> <b>Scope</b> .....	<b>5</b>
<b>2</b> <b>Definitions</b> .....	<b>5</b>
<b>3</b> <b>Symbols and units</b> .....	<b>6</b>
<b>4</b> <b>Principle</b> .....	<b>6</b>
<b>5</b> <b>Apparatus</b> .....	<b>7</b>
<b>6</b> <b>Test specimens</b> .....	<b>9</b>
<b>6.1</b> <b>Materials <math>\leq 5</math> mm thick</b> .....	<b>9</b>
<b>6.2</b> <b>Materials <math>&gt; 5</math> mm thick</b> .....	<b>9</b>
<b>7</b> <b>Test procedure</b> .....	<b>10</b>
<b>7.1</b> <b>Determination of apparatus constants</b> .....	<b>10</b>
<b>7.1.1</b> <b>Determination of <math>R_{ct0}</math></b> .....	<b>10</b>
<b>7.1.2</b> <b>Determination of <math>R_{et0}</math></b> .....	<b>10</b>
<b>7.1.3</b> <b>Reference material</b> .....	<b>10</b>
<b>7.1.4</b> <b>Recalibration</b> .....	<b>10</b>
<b>7.2</b> <b>Assembly of test specimens on the measuring unit</b> .....	<b>10</b>
<b>7.3</b> <b>Measurement of thermal resistance <math>R_{ct}</math></b> .....	<b>11</b>
<b>7.4</b> <b>Measurement of water-vapour resistance <math>R_{et}</math></b> .....	<b>11</b>
<b>8</b> <b>Precision of results</b> .....	<b>11</b>
<b>8.1</b> <b>Repeatability</b> .....	<b>11</b>
<b>8.2</b> <b>Reproducibility</b> .....	<b>12</b>
<b>9</b> <b>Test report</b> .....	<b>12</b>
<b>Annex A (normative) Mounting procedure for specimens containing loose filling materials or having uneven thickness</b> .....	<b>13</b>
<b>Annex B (normative) Determination of corrections terms for heating power</b> .....	<b>14</b>
<b>[A1]</b> <b>Annex C (informative) Guidance on test specimen assembly for materials prone to swelling</b> .....	<b>15</b>
<b>C.1</b> <b>General</b> .....	<b>15</b>
<b>C.2</b> <b>Additional guidance for a test specimen assembly for materials prone to swelling</b> .....	<b>15</b>