

ISO 8311:2013-12 (E)

Refrigerated hydrocarbon and non-petroleum based liquefied gaseous fuels - Calibration of membrane tanks and independent prismatic tanks in ships - Manual and internal electro-optical distance-ranging methods

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Precautions	3
4.1	General	3
4.2	Ship's condition during calibration	3
4.3	Tank distortion	3
4.4	Comparison with drawings	4
4.5	Measurements by measuring tape	4
4.6	Measurements by electro-optical distance-ranging (EODR) instrument	4
4.7	Condition of membrane	5
4.8	Safety precautions for work in membrane tanks	5
5	Equipment	5
6	Determination of measuring points	6
7	Calibration by manual method	6
7.1	General	6
7.2	Tank length measurement	7
7.3	Tank width measurement	9
7.4	Tank height measurement	12
7.5	Measurement of bottom undulation and gauge reference height	14
7.6	Correction for temperature	15
8	Calibration by electro-optical distance-ranging (EODR) method	16
8.1	General	16
8.2	Setting up of EODR instrument	16
8.3	Calibration procedure	17
9	Additional measurements	19
9.1	Location of level gauge	19
9.2	Deadwood	19
10	Calculation	19
10.1	General	19
10.2	Calculation of tank volume	20
10.3	Effect of bottom undulation	20
10.4	Area of chamfer portion	20
10.5	Trim corrections	21
10.6	List corrections	21
10.7	Combined trim and list corrections	21

10.8	Correction for tank shell expansion or contraction	21
11	Report and tables	22
12	Recalibration	23
	Annex A (informative) Uncertainty associated with tank calibration	24
	Annex B (informative) Example of tank capacity table (Tank No.3)	36
	Annex C (informative) Example of trim correction table (Tank No. 1)	38
	Annex D (informative) Example of list correction table (Tank No. 1)	40
	Bibliography	42