

DIN EN ISO 16828:2014-06 (E)

Non-destructive testing - Ultrasonic testing - Time-of-flight diffraction technique as a method for detection and sizing of discontinuities (ISO 16828:2012)

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms, definitions, symbols and abbreviations	7
3.1 Terms and definitions	7
3.2 Abbreviations	7
3.3 Symbols	7
4 General	8
4.1 Principle of the technique	8
4.2 Requirements for surface condition and couplant	10
4.3 Materials and process type	10
5 Qualification of personnel	10
6 Equipment requirements	10
6.1 Ultrasonic equipment and display	10
6.2 Ultrasonic probes	11
6.3 Scanning mechanisms	12
7 Equipment set-up procedures	12
7.1 General	12
7.2 Probe choice and probe separation	13
7.2.1 Probe selection	13
7.2.2 Probe separation	14
7.3 Time window setting	14
7.4 Sensitivity setting	14
7.5 Scan resolution setting	15
7.6 Setting of scanning speed	15
7.7 Checking system performance	15
8 Interpretation and analysis of data	15
8.1 Basic analysis of discontinuities	15
8.1.1 General	15
8.1.2 Characterisation of discontinuities	15
8.1.3 Estimation of discontinuity position	16
8.1.4 Estimation of discontinuity length	16
8.1.5 Estimation of discontinuity depth and height	17
8.2 Detailed analysis of discontinuities	17
8.2.1 General	17
8.2.2 Additional scans	18
8.2.3 Additional algorithms	19
9 Detection and sizing in complex geometries	19

10	Limitations of the technique.....	19
10.1	General	19
10.2	Accuracy and resolution.....	20
10.2.1	General	20
10.2.2	Errors in the lateral position	20
10.2.3	Timing errors	20
10.2.4	Errors in sound velocity	20
10.2.5	Errors in probe centre separation	20
10.2.6	Spatial resolution	21
10.3	Dead zones.....	21
11	TOFD examination without data recording	21
12	Test procedure	22
13	Test report	22
Annex A (normative) Reference blocks		23
Bibliography		24