

# ISO 13935-2:2014-03 (E)

## Textiles - Seam tensile properties of fabrics and made-up textile articles - Part 2: Determination of maximum force to seam rupture using the grab method

---

Contents	Page
<b>Foreword</b> .....	iv
<b>Introduction</b> .....	v
<b>1 Scope</b> .....	1
<b>2 Normative references</b> .....	1
<b>3 Terms and definitions</b> .....	1
<b>4 Principle</b> .....	2
<b>5 Sampling</b> .....	2
<b>6 Apparatus</b> .....	2
<b>7 Atmosphere for conditioning and testing</b> .....	3
<b>8 Preparation of seams and of test specimens</b> .....	3
<b>8.1 Preparation of seams, if required, before testing</b> .....	3
<b>8.2 Dimensions</b> .....	3
<b>8.3 Preparation of test specimens</b> .....	4
<b>9 Procedure</b> .....	5
<b>9.1 Gauge length</b> .....	5
<b>9.2 Rate of extension</b> .....	5
<b>9.3 Mounting of test specimens</b> .....	5
<b>9.4 Operation</b> .....	6
<b>10 Calculation and expression of results</b> .....	6
<b>11 Test report</b> .....	6
<b>Annex A (informative) Arrangements of jaws for the grab test</b> .....	8
<b>Bibliography</b> .....	9