

DIN EN ISO 13935-2:2014-07 (E)

Textiles - Seam tensile properties of fabrics and made-up textile articles - Part 2:
Determination of maximum force to seam rupture using the grab method (ISO 13935-
2:2014)

| Contents | | Page |
|--|---|-------------|
| Foreword | | 3 |
| Introduction | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Principle | 6 |
| 5 | Sampling | 6 |
| 6 | Apparatus | 6 |
| 7 | Atmosphere for conditioning and testing | 7 |
| 8 | Preparation of seams and of test specimens | 7 |
| 8.1 | Preparation of seams, if required, before testing | 7 |
| 8.2 | Dimensions | 7 |
| 8.3 | Preparation of test specimens | 8 |
| 9 | Procedure | 9 |
| 9.1 | Gauge length | 9 |
| 9.2 | Rate of extension | 9 |
| 9.3 | Mounting of test specimens | 9 |
| 9.4 | Operation | 10 |
| 10 | Calculation and expression of results | 10 |
| 11 | Test report | 10 |
| Annex A (informative) Arrangements of jaws for the grab test | | 11 |
| Bibliography | | 12 |