

# ISO 5164:2014-06 (E)

## Petroleum products - Determination of knock characteristics of motor fuels - Research method

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	1
4	Principle .....	3
5	Reagents and reference materials .....	3
6	Apparatus .....	5
7	Sampling and sample preparation .....	6
8	Basic engine and instrument settings and standard operating conditions .....	6
8.1	Installation of engine equipment and instrumentation .....	6
8.2	Engine speed .....	6
8.3	Valve timing .....	7
8.4	Valve lift .....	7
8.5	Intake valve shroud .....	7
8.6	Carburettor venturi .....	7
8.7	Direction of engine rotation .....	7
8.8	Valve clearances .....	7
8.9	Oil pressure .....	7
8.10	Oil temperature .....	8
8.11	Cylinder jacket coolant temperature .....	8
8.12	Intake air temperature .....	8
8.13	Intake air humidity .....	8
8.14	Cylinder jacket coolant level .....	8
8.15	Engine crankcase lubricating oil level .....	9
8.16	Crankcase internal pressure .....	9
8.17	Exhaust back-pressure .....	9
8.18	Exhaust and crankcase breather system resonance .....	9
8.19	Belt tension .....	9
8.20	Rocker arm carrier support basic setting .....	9
8.21	Rocker arm carrier basic setting .....	9
8.22	Rocker arm and push rod length basic settings .....	9
8.23	Basic spark setting .....	10
8.24	Basic ignition timer control arm setting .....	10
8.25	Basic ignition timer transducer to rotor vane gap setting .....	10
8.26	Spark-plug gap .....	10
8.27	Basic cylinder height setting .....	10
8.28	Fuel-air ratio .....	11
8.29	Carburettor cooling .....	12
8.30	Knockmeter reading limits .....	12
8.31	Detonation meter spread and time constant settings .....	12

<b>9</b>	<b>Engine calibration and qualification .....</b>	<b>12</b>
<b>9.1</b>	<b>General .....</b>	<b>12</b>
<b>9.2</b>	<b>Engine fit-for-use qualification .....</b>	<b>12</b>
<b>9.3</b>	<b>Fit-for-use procedure in the 87,1 RON to 100,0 RON range .....</b>	<b>13</b>
<b>9.4</b>	<b>Fit-for-use procedure below 87,1 RON and above 100,0 RON .....</b>	<b>14</b>
<b>9.5</b>	<b>Checking performance on check fuels .....</b>	<b>14</b>
<b>10</b>	<b>Procedure .....</b>	<b>15</b>
<b>10.1</b>	<b>General .....</b>	<b>15</b>
<b>10.2</b>	<b>Start-up .....</b>	<b>15</b>
<b>10.3</b>	<b>Calibration .....</b>	<b>15</b>
<b>10.4</b>	<b>Sample fuel .....</b>	<b>16</b>
<b>10.5</b>	<b>Primary reference fuel No. 1 .....</b>	<b>16</b>
<b>10.6</b>	<b>Primary reference fuel No. 2 .....</b>	<b>17</b>
<b>10.7</b>	<b>Additional measurement readings .....</b>	<b>17</b>
<b>10.8</b>	<b>Special instructions for ratings above 100,0 RON .....</b>	<b>17</b>
<b>11</b>	<b>Calculation .....</b>	<b>18</b>
<b>12</b>	<b>Expression of results .....</b>	<b>18</b>
<b>13</b>	<b>Precision .....</b>	<b>19</b>
<b>13.1</b>	<b>General .....</b>	<b>19</b>
<b>13.2</b>	<b>Repeatability, r .....</b>	<b>19</b>
<b>13.3</b>	<b>Reproducibility, R .....</b>	<b>19</b>
<b>13.4</b>	<b>Precision for ratings at barometric pressures below 94,6 kPa .....</b>	<b>19</b>
<b>13.5</b>	<b>Precision for fuels containing 15% to 25% (V/V) ethanol .....</b>	<b>20</b>
<b>14</b>	<b>Test report .....</b>	<b>20</b>
	<b>Annex A (informative) Test variable characteristics .....</b>	<b>21</b>
	<b>Bibliography .....</b>	<b>24</b>