

# ISO 815-1:2014-09 (E)

## Rubber, vulcanized or thermoplastic - Determination of compression set - Part 1: At ambient or elevated temperatures

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Principle .....</b>	<b>2</b>
<b>4</b>	<b>Apparatus .....</b>	<b>2</b>
<b>5</b>	<b>Calibration .....</b>	<b>3</b>
<b>6</b>	<b>Test pieces .....</b>	<b>4</b>
<b>6.1</b>	<b>Dimensions .....</b>	<b>4</b>
<b>6.2</b>	<b>Preparation .....</b>	<b>4</b>
<b>6.3</b>	<b>Number of test pieces .....</b>	<b>4</b>
<b>6.4</b>	<b>Time interval between production and testing .....</b>	<b>4</b>
<b>6.5</b>	<b>Conditioning .....</b>	<b>5</b>
<b>7</b>	<b>Test conditions .....</b>	<b>5</b>
<b>7.1</b>	<b>Duration of test .....</b>	<b>5</b>
<b>7.2</b>	<b>Temperature of test .....</b>	<b>5</b>
<b>8</b>	<b>Procedure .....</b>	<b>5</b>
<b>8.1</b>	<b>Preparation of compression assembly .....</b>	<b>5</b>
<b>8.2</b>	<b>Thickness measurement .....</b>	<b>5</b>
<b>8.3</b>	<b>Applying the compression .....</b>	<b>6</b>
<b>8.4</b>	<b>Starting the test .....</b>	<b>6</b>
<b>8.5</b>	<b>Terminating the test .....</b>	<b>6</b>
<b>8.6</b>	<b>Internal examination .....</b>	<b>6</b>
<b>9</b>	<b>Expression of results .....</b>	<b>7</b>
<b>10</b>	<b>Precision .....</b>	<b>7</b>
<b>11</b>	<b>Test report .....</b>	<b>7</b>
<b>Annex A (informative) Precision .....</b>		<b>9</b>
<b>Annex B (normative) Calibration schedule .....</b>		<b>11</b>
<b>Bibliography .....</b>		<b>13</b>