

# DIN 25457-1:2014-12 (E)

## Activity measurement methods for the clearance of radioactive substances and nuclear facility components - Part 1: Fundamentals

---

<b>Contents</b>	<b>Page</b>
Foreword .....	5
<b>1 Scope .....</b>	<b>6</b>
<b>2 Normative references .....</b>	<b>6</b>
<b>3 Terms, definitions and symbols .....</b>	<b>7</b>
<b>3.1 Terms and definitions.....</b>	<b>7</b>
<b>3.2 Symbols .....</b>	<b>9</b>
<b>4 Measurement methods.....</b>	<b>13</b>
<b>4.1 Basic model and characteristic variables of the activity measurement methods with consideration of type A and type B measuring uncertainties.....</b>	<b>13</b>
<b>4.1.1 General information.....</b>	<b>13</b>
<b>4.1.2 Description of the model in general form .....</b>	<b>14</b>
<b>4.1.3 Special model approach for activity measurement method.....</b>	<b>15</b>
<b>4.1.4 Procedure for conservative and realistic approaches .....</b>	<b>17</b>
<b>4.2 Direct surface-total-activity measurement.....</b>	<b>18</b>
<b>4.2.1 General .....</b>	<b>18</b>
<b>4.2.2 Relevant type B measurement uncertainties.....</b>	<b>19</b>
<b>4.2.3 Requirements for the measurement devices .....</b>	<b>20</b>
<b>4.2.4 Requirements for the calibration sources .....</b>	<b>20</b>
<b>4.2.5 State of the surface of the measured material .....</b>	<b>21</b>
<b>4.2.6 Dependency of the count rate of the detector on the geometric conditions .....</b>	<b>21</b>
<b>4.2.7 Determination of an alarm value .....</b>	<b>21</b>
<b>4.2.8 Measurement procedure .....</b>	<b>23</b>
<b>4.2.9 Quality assurance.....</b>	<b>25</b>
<b>4.3 Indirect surface total-activity measurement .....</b>	<b>26</b>
<b>4.3.1 General .....</b>	<b>26</b>
<b>4.3.2 Relevant type B measurement uncertainties.....</b>	<b>26</b>
<b>4.3.3 Requirements for the measurement setup.....</b>	<b>27</b>
<b>4.3.4 Requirements for the calibration source .....</b>	<b>27</b>
<b>4.3.5 Calibration.....</b>	<b>27</b>
<b>4.3.6 Background effect determination.....</b>	<b>27</b>
<b>4.3.7 Performing the measurement.....</b>	<b>27</b>
<b>4.3.8 Quality assurance.....</b>	<b>28</b>
<b>4.4 Spectrometric measurement methods.....</b>	<b>29</b>
<b>4.4.1 Gamma spectrometry on material samples.....</b>	<b>29</b>
<b>4.4.2 In-situ gamma spectrometry .....</b>	<b>36</b>
<b>4.4.3 Alpha spectrometry on material samples .....</b>	<b>42</b>
<b>4.4.4 Determination of the activity of alpha-emitting radionuclides using gamma spectrometry on material samples.....</b>	<b>47</b>
<b>4.5 Total gamma activity measurement .....</b>	<b>47</b>
<b>4.5.1 General .....</b>	<b>47</b>
<b>4.5.2 Relevant measurement uncertainties .....</b>	<b>48</b>
<b>4.5.3 Requirements for measurement equipment.....</b>	<b>48</b>
<b>4.5.4 Property of the measured material.....</b>	<b>48</b>
<b>4.5.5 Requirements for the calibration .....</b>	<b>48</b>
<b>4.5.6 Performing the measurement.....</b>	<b>49</b>
<b>4.5.7 Detection limit, decision threshold and confidence interval.....</b>	<b>49</b>
<b>4.5.8 Quality assurance.....</b>	<b>50</b>

<b>Annex A (normative) Determination of the surface response .....</b>	<b>52</b>
<b>Annex B (informative) Energies and range of alpha particles .....</b>	<b>57</b>
<b>Annex C (informative) Determination of the activity of alpha-emitting radionuclides using gamma spectrometry on material specimens.....</b>	<b>59</b>
<b>C.1 General.....</b>	<b>59</b>
<b>C.2 Thorium decay series and Th-230 .....</b>	<b>59</b>
<b>C.3 Uranium.....</b>	<b>59</b>
<b>C.4 Plutonium .....</b>	<b>60</b>
<b>Annex D (informative) Explanations for the calculation of the decision thresholds and detection limits for the pulse counting with time preselection.....</b>	<b>64</b>
<b>Annex E (informative) Explanations for the calculation of the detection limit and decision threshold for stationary pulse rate measurements .....</b>	<b>69</b>
<b>Annex F (informative) Explanations for the calculation of the detection limit and decision threshold for dynamic pulse rate measurement.....</b>	<b>79</b>
<b>Annex G (informative) Explanations for the calculation of the decision thresholds and detection limits for the pulse counting with time preselection at small pulse numbers, e.g. alpha surface activity measurement.....</b>	<b>82</b>
<b>Annex H (informative) Calculation of the detection limit and decision threshold, the upper limit of the confidence interval and the expected value for measurements using contamination monitors with consideration of type B measurement uncertainties.....</b>	<b>84</b>
<b>H.1 Basic measurement model .....</b>	<b>84</b>
<b>H.2 Measurement task and measurement parameters .....</b>	<b>85</b>
<b>H.3 Calculation of the characteristic variables.....</b>	<b>86</b>
<b>H.4 Interpretation of the results in respect of the decision measurement for the clearance.....</b>	<b>87</b>
<b>H.5 Integration of uncertainties in respect of the clearance level of the area-specific total activity .....</b>	<b>88</b>
<b>Annex I (informative) Calculation of the detection limit and decision threshold for measurements with wipe test measurement setups (indirect total surface activity measurement) .....</b>	<b>89</b>
<b>Annex J (informative) Calculation of the detection limit and decision threshold, the upper limit of the confidence interval and the expected value for gamma spectrometry and in-situ gamma spectrometry .....</b>	<b>92</b>
<b>J.1 Preliminary remarks.....</b>	<b>92</b>
<b>J.2 Measurement of site grounds according to DIN 25457-7: Determination of the area- specific activity as well as the nuclide-specific dose rate of Cs-137.....</b>	<b>92</b>
<b>J.2.1 General.....</b>	<b>92</b>
<b>J.2.2 Calibration factor and its standard uncertainty.....</b>	<b>93</b>
<b>J.2.3 Calculation of the nuclide-specific ambient dose equivalent rate.....</b>	<b>93</b>
<b>J.2.4 Example for the calculation of the characteristic limits as well as the best estimator and its standard uncertainty (non-collimated measurement, area-specific activity and nuclide-specific dose rate) .....</b>	<b>94</b>
<b>J.2.5 Summary .....</b>	<b>96</b>
<b>J.3 Determination of the mass-specific activity if a disturbance is present due to an interfering line as well as a line in the background effect spectrum.....</b>	<b>96</b>
<b>J.4 Determination of the Co-60 activity from very small net peak areas.....</b>	<b>98</b>
<b>Annex K (informative) Calculation of the detection limit and the decision threshold, the upper limit of the confidence interval and the expected value for total gamma activity measurements.....</b>	<b>104</b>
<b>K.1 Preliminary remarks.....</b>	<b>104</b>
<b>K.2 Essential input variables for the conservative calibration .....</b>	<b>105</b>
<b>K.3 Realistic calculation of decision threshold and detection limit .....</b>	<b>108</b>
<b>K.3.1 General .....</b>	<b>108</b>
<b>K.3.2 Determination of the realistic calibration factor <math>w</math>.....</b>	<b>108</b>
<b>K.3.3 Consideration of the reduction of the background effect due to measured material.....</b>	<b>108</b>
<b>K.3.4 Consideration of the non-counting statistical variance of the background effect .....</b>	<b>108</b>
<b>K.4 Best estimated values, upper limit of the confidence interval .....</b>	<b>111</b>
<b>K.5 Summary .....</b>	<b>114</b>
<b>Bibliography .....</b>	<b>116</b>