

ISO 18560-1:2014-11 (E)

Fine ceramics (advanced ceramic s, advanced technical ceramics) - Test method for air-purification performance of semiconducting photocatalytic materials by test chamber method under indoor lighting environment - Part 1: Removal of formaldehyde

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Symbols	3
5	Principle	4
6	Apparatus	4
6.1	General	4
6.2	Test chamber	5
6.3	Sealing material for test specimens	5
6.4	Air purifier	5
6.5	Supply air spiked with formaldehyde	6
6.6	Temperature and humidity controls	6
6.7	Air flow meter	6
6.8	Light source and UV sharp cut-off filter	6
6.9	Air sampling devices	6
6.10	Device to circulate air and control of air velocity	6
6.11	Analytical instrument	7
7	Test conditions	7
7.1	General	7
7.2	Test conditions of removal performance	7
7.3	Factors affecting the removal performance (optional)	8
8	Verification of test conditions	9
8.1	Monitoring of test conditions	9
8.2	Air-tightness of test chamber	9
8.3	Air change rate in test chamber	9
8.4	Efficiency of the internal test chamber air mixing	9
8.5	Recovery	9
9	Preparation of test chamber	9
10	Test specimen	10
10.1	Preparation of test specimen	10
10.2	Preparation for the test	10
11	Test methods	10
11.1	Background concentration and supply air spiked with formaldehyde	10
11.2	Placing the test specimen in the test chamber	10
11.3	Test under dark condition	10
11.4	Test for removal performance	11

11.5	Factors affecting the removal performance	11
11.6	Air sampling	11
12	Determination of formaldehyde	11
13	Calculation and expression of results	11
14	Test report	12
Annex A (informative) Example of a test chamber		14
Bibliography		17