

DIN EN ISO 6892-1:2017-02 (E)

Metallic materials - Tensile testing - Part 1: Method of test at room temperature (ISO 6892-1:2016)

Contents	Page
European foreword.....	4
Foreword	5
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	7
4 Symbols	12
5 Principle	13
6 Test pieces	14
6.1 Shape and dimensions	14
6.1.1 General	14
6.1.2 Machined test pieces	14
6.1.3 Unmachined test pieces	15
6.2 Types	15
6.3 Preparation of test pieces	15
7 Determination of original cross-sectional area	15
8 Original gauge length and extensometer gauge length	16
8.1 Choice of the original gauge length	16
8.2 Marking the original gauge length	16
8.3 Choice of the extensometer gauge length	16
9 Accuracy of testing apparatus	16
10 Conditions of testing	17
10.1 Setting the force zero point	17
10.2 Method of gripping	17
10.3 Testing rates	17
10.3.1 General information regarding testing rates	17
10.3.2 Testing rate based on strain rate (method A)	17
10.3.3 Testing rate based on stress rate (method B)	19
10.3.4 Report of the chosen testing conditions	21
11 Determination of the upper yield strength	21
12 Determination of the lower yield strength	21
13 Determination of proof strength, plastic extension	21
14 Determination of proof strength, total extension	22
15 Method of verification of permanent set strength	22
16 Determination of the percentage yield point extension	22
17 Determination of the percentage plastic extension at maximum force	23
18 Determination of the percentage total extension at maximum force	23
19 Determination of the percentage total extension at fracture	23

20	Determination of percentage elongation after fracture.....	24
21	Determination of percentage reduction of area.....	24
22	Test report.....	25
23	Measurement uncertainty	26
23.1	General.....	26
23.2	Test conditions.....	26
23.3	Test results.....	26
Annex A (informative) Recommendations concerning the use of computer-controlled tensile testing machines		40
Annex B (normative) Types of test pieces to be used for thin products: sheets, strips, and flats between 0,1 mm and 3 mm thick.....		46
Annex C (normative) Types of test pieces to be used for wire, bars, and sections with a diameter or thickness of less than 4 mm.....		49
Annex D (normative) Types of test pieces to be used for sheets and flats of thickness equal to or greater than 3 mm and wire, bars, and sections of diameter or thickness equal to or greater than 4 mm		50
Annex E (normative) Types of test pieces to be used for tubes		53
Annex F (informative) Estimation of the crosshead separation rate in consideration of the stiffness (or compliance) of the testing equipment.....		55
Annex G (normative) Determination of the modulus of elasticity of metallic materials using a uniaxial tensile test.....		57
Annex H (informative) Measuring the percentage elongation after fracture if the specified value is less than 5 %.....		66
Annex I (informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length		67
Annex J (informative) Determination of the percentage plastic elongation without necking, A_{wn} , for long products such as bars, wire, and rods.....		69
Annex K (informative) Estimation of the uncertainty of measurement		70
Annex L (informative) Precision of tensile testing — Results from interlaboratory programmes ..		74
Bibliography		81