

# DIN EN ISO 18081:2016-11 (E)

## Non-destructive testing - Acoustic emission testing (AT) - Leak detection by means of acoustic emission (ISO 18081:2016)

---

| <b>Contents</b>          |   | <b>Page</b> |
|--------------------------|---|-------------|
| <b>European foreword</b> |   | <b>4</b>    |
| <b>Foreword</b>          |   | <b>5</b>    |
| <b>1</b>                 | <b>Scope</b>  | <b>6</b>    |
| <b>2</b>                 | <b>Normative references</b>   | <b>6</b>    |
| <b>3</b>                 | <b>Terms and definitions</b>  | <b>6</b>    |
| <b>4</b>                 | <b>Personnel qualification</b>  | <b>7</b>    |
| <b>5</b>                 | <b>Principle of acoustic emission method</b>                              | <b>7</b>    |
| 5.1                      | The AE phenomenon   | 7           |
| 5.2                      | Influence of different media and different phases                         | 8           |
| 5.3                      | Influence of pressure differences   | 9           |
| 5.4                      | Influence of geometry of the leak path                                    | 9           |
| 5.5                      | Influence of wave propagation   | 9           |
| <b>6</b>                 | <b>Applications</b>   | <b>10</b>   |
| <b>7</b>                 | <b>Instrumentation</b>  | <b>10</b>   |
| 7.1                      | General requirements  | 10          |
| 7.2                      | Sensors   | 10          |
| 7.2.1                    | Typical frequency ranges (band widths)                                    | 10          |
| 7.2.2                    | Mounting method   | 11          |
| 7.2.3                    | Temperature range, wave guide   | 11          |
| 7.2.4                    | Intrinsic safety  | 11          |
| 7.2.5                    | Immersed sensors  | 11          |
| 7.2.6                    | Integral electronics (amplifier, RMS converter, ASL converter, band pass) | 11          |
| 7.3                      | Portable and non-portable AT instruments                                  | 11          |
| 7.4                      | Single and multichannel AT equipment                                      | 11          |
| 7.4.1                    | Single-channel systems  | 11          |
| 7.4.2                    | Multi-channel systems   | 11          |
| 7.5                      | Measuring features (RMS, ASL vs. hit or continuous AE vs. burst AE)       | 12          |
| 7.6                      | Verification using artificial leak noise sources                          | 12          |
| <b>8</b>                 | <b>Test steps for leak detection</b>                                      | <b>12</b>   |
| 8.1                      | Sensor application  | 12          |
| 8.2                      | Measured features   | 13          |
| 8.3                      | Background noise  | 13          |
| 8.3.1                    | Environmental noise   | 13          |
| 8.3.2                    | Process noise   | 13          |
| 8.4                      | Data acquisition  | 13          |
| <b>9</b>                 | <b>Location procedures</b>  | <b>14</b>   |
| 9.1                      | General considerations  | 14          |
| 9.2                      | Single sensor location based on AE wave attenuation                       | 14          |
| 9.3                      | Multi-sensor location based on $\Delta t$ values (linear, planar)         | 14          |
| 9.3.1                    | Threshold level and peak level timing method                              | 14          |
| 9.3.2                    | Cross correlation method  | 15          |
| 9.4                      | Wave type and wave mode based location                                    | 16          |

|   |   |           |
|---|---|-----------|
| <b>10</b>   | <b>Data presentation</b> .....                          | <b>16</b> |
| 10.1  | Numerical data presentation (level-meter).....          | 16        |
| 10.2  | Parametric dependent function (e.g. pressure).....      | 16        |
| 10.3  | Frequency spectrum.....                                 | 17        |
| <b>11</b>   | <b>Data interpretation</b> .....                        | <b>17</b> |
| 11.1  | Leak validation.....                                    | 17        |
| 11.1.1  | On-site (during test) and off-site (post analysis)..... | 17        |
| 11.1.2  | Correlation with pressure.....                          | 17        |
| 11.1.3  | Rejection of false indications.....                     | 17        |
| 11.2  | Leakage rate estimation.....                            | 18        |
| 11.3  | Demands on follow-up actions.....                       | 18        |
| <b>12</b>   | <b>Quality management documents</b> .....               | <b>18</b> |
| 12.1  | Test procedure.....                                     | 18        |
| 12.2  | Test instruction.....                                   | 18        |
| <b>13</b>   | <b>Test documentation and reporting</b> .....           | <b>19</b> |
| 13.1  | Test documentation.....                                 | 19        |
| 13.2  | Test report.....  | 20        |
| <b>Annex A (normative) Examples of leak detection</b> ..... |   | <b>21</b> |
| <b>Bibliography</b> .....                                   |   | <b>33</b> |