DIN EN 16846-1:2017-05 (E)

Photocatalysis - Measurement of efficiency of photocatalytic devices used for the elimination of VOC and odour in indoor air in active mode - Part 1: Batch mode test method in closed chamber

Contents

Page

European foreword 3

1 Scope 4

2 Normative references 4

3 Terms and definitions 4

4 Symbols and abbreviations 5

5 Principle 5

6 Apparatus 6

7 Test performance 6
7.1 Pollutants and concentrations 6
7.1.1 General 6
7.1.2 Indoor air 6
7.1.3 Industrial issue and challenge 7
7.2 Validation of the chamber 7
7.3 Test conditions 7
7.4 Test procedure 7
7.5 Mineralization test with continuous monitoring of CO2 levels 7
7.6 Analysis of reaction by-products and ozone 8
7.7 Olfactive efficiency of the system 8

8 Test report 9

Annex A (informative) Schematic diagram of an air tight chamber 10

Annex B (informative) Types of sorbent apparatus for thermal desorption cartridges 11

Annex C (informative) Examples of a chamber blanks analysis 12

Annex D (informative) Analysis of the reaction mixture 13

Annex E (informative) Example of a plot of temperature and relative humidity, as well as developments in pollutants and CO2 14

Annex F (informative) Example of test at low concentration with formaldehyde 16

Annex G (informative) CADR calculation 17

Annex H (informative) Calculation of CADR 19