

DIN EN 16846-1:2017-05 (E)

Photocatalysis - Measurement of efficiency of photocatalytic devices used for the elimination of VOC and odour in indoor air in active mode - Part 1: Batch mode test method in closed chamber

| Contents | Page |
|---|-------------|
| European foreword | 3 |
| 1 Scope | 4 |
| 2 Normative references | 4 |
| 3 Terms and definitions | 4 |
| 4 Symbols and abbreviations | 5 |
| 5 Principle | 5 |
| 6 Apparatus | 6 |
| 7 Test performance | 6 |
| 7.1 Pollutants and concentrations | 6 |
| 7.1.1 General | 6 |
| 7.1.2 Indoor air | 6 |
| 7.1.3 Industrial issue and challenge | 7 |
| 7.2 Validation of the chamber | 7 |
| 7.3 Test conditions | 7 |
| 7.4 Test procedure | 7 |
| 7.5 Mineralization test with continuous monitoring of CO ₂ levels | 7 |
| 7.6 Analysis of reaction by-products and ozone | 8 |
| 7.7 Olfactive efficiency of the system | 8 |
| 8 Test report | 9 |
| Annex A (informative) Schematic diagram of an air tight chamber | 10 |
| Annex B (informative) Types of sorbent apparatus for thermal desorption cartridges | 11 |
| Annex C (informative) Examples of a chamber blanks analysis | 12 |
| Annex D (informative) Analysis of the reaction mixture | 13 |
| Annex E (informative) Example of a plot of temperature and relative humidity, as well as developments in pollutants and CO ₂ | 14 |
| Annex F (informative) Example of test at low concentration with formaldehyde | 16 |
| Annex G (informative) CADR calculation | 17 |
| Annex H (informative) Calculation of CADR | 19 |