

DIN EN 16846-1:2017-05 (E)

Photocatalysis - Measurement of efficiency of photocatalytic devices used for the elimination of VOC and odour in indoor air in active mode - Part 1: Batch mode test method in closed chamber

Contents	Page
European foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Symbols and abbreviations	5
5 Principle	5
6 Apparatus	6
7 Test performance	6
7.1 Pollutants and concentrations	6
7.1.1 General	6
7.1.2 Indoor air	6
7.1.3 Industrial issue and challenge	7
7.2 Validation of the chamber	7
7.3 Test conditions	7
7.4 Test procedure	7
7.5 Mineralization test with continuous monitoring of CO ₂ levels	7
7.6 Analysis of reaction by-products and ozone	8
7.7 Olfactive efficiency of the system	8
8 Test report	9
Annex A (informative) Schematic diagram of an air tight chamber	10
Annex B (informative) Types of sorbent apparatus for thermal desorption cartridges	11
Annex C (informative) Examples of a chamber blanks analysis	12
Annex D (informative) Analysis of the reaction mixture	13
Annex E (informative) Example of a plot of temperature and relative humidity, as well as developments in pollutants and CO ₂	14
Annex F (informative) Example of test at low concentration with formaldehyde	16
Annex G (informative) CADR calculation	17
Annex H (informative) Calculation of CADR	19