

ISO 4590:2016-07 (E)

Rigid cellular plastics - Determination of the volume percentage of open cells and of closed cells

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Test specimens	2
5.1	Number	2
5.2	Preparation	3
5.3	Dimensions	3
5.4	Sectioning of test specimens	3
6	Conditioning and test atmospheres	3
7	Measurement of surface area S and geometrical volume V_g	3
8	Determination of impenetrable volume V_i by method 1: pressure variation (pycnometer)4	
8.1	Principle of method 1	5
8.2	Description of apparatus for method 1	5
8.3	Calibration of pycnometer apparatus	7
8.4	Procedure for method 1	8
8.5	Calculation for method 1	9
9	Determination of impenetrable volume V_i by method 2: volume expansion	9
9.1	Principle of method 2	9
9.2	Description of apparatus for method 2a	10
9.3	Calibration of apparatus for method 2a	11
9.4	Procedure and calculation for method 2a	14
9.5	Description of apparatus for method 2b	14
9.6	Calibration of apparatus for method 2b	15
9.7	Test procedure for method 2b	15
9.8	Test sequence for method 2b	16
9.9	Calculations and expression of results for method 2b	17
10	Correction for specimen surface cells opened during specimen preparation	17
10.1	For the pressure-variation method (see Clause 8)	17
10.2	For the volume-expansion method (see Clause 9)	17
11	Expression of results	18
11.1	Apparent volume percentage of open cells	18
11.2	Corrected volume percentage of open cells	18
12	Precision	19
13	Test report	20
Annex A (normative) Notes on procedure		21